



PRAMAC GBW15Y ENCLOSURE WITH MANUAL CONTROL PANEL



Product price:

9.465,00 € tax excluded

Product description:

Generator PRAMAC GBW15Y MCP Three-phase 11.4 KW Supersilenced

11.4 KW three-phase PRAMAC GBW15Y generator with diesel engine at 1500 rpm. The PRAMAC GBW15Y generator set is equipped with an electric start. The PRAMAC GBW15Y generator set alternator is with brushes with **compound** voltage regulator. The Yanmar diesel engine makes the GBW15Y generator set **very reliable** as it has been built and designed using high quality materials.

Thanks to its canopy this generator set is **super silenced**. In addition it is easy to transport, install and position thanks to its compact size, this model is ideal for network emergencies, construction, mobile workshops and industrial applications. The PRAMAC GBW15Y three-phase generator set is suitable for outdoor use on construction sites or for small professional jobs outside.

Technical characteristics of the PRAMAC GBW15Y Three-phase generator set:

Phase type: Single-phase / Three-phase

Maximum three-phase power: 13.5 KVA / 11.44 KW

Continuous use three-phase power: 12.6 KVA / 10.4 KW

Fuel: Diesel

Voltage: 230/400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV88-BGPGE

Starting: Electric

Consumption: 3.8 Lt / h at 100% of the load

Length: 1645 mm

Width: 870 mm

Height: 1072 mm



Weight: 430 Kg
Compound

Sockets:

N.1 3P + N + T CEE 400V 32A
N.1 3P + N + T CEE 400V 16A
N.2 2P + T CEE 230V 16A
N. 1 230V 16A SCHUKO

The PRAMAC GBW15Y current generator is a professional diesel generator set developed by Pramac with features and equipment necessary to obtain a class product on par. The PRAMAC GBW15Y power generator with low noise level is the ideal generator for use in residential areas or in non-working hours.

The GBW15Y generator set is equipped with a reliable diesel engine, top quality components and a complete instrumentation.

If you are looking for a generator such as the three-phase GBW15Y current generator then we recommend that you browse our catalog of land-based generators to find the one that is closest to your needs.

Pictures and technical data are not binding.

Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 10.8

Continuous power three phase (KW): 10

Maximum power three phase (KVA): 13.5

Continuous power three phase (KVA): 12.6

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar 3TNV88-BGPGE, naturally aspirated

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 1642

Number cylinders: 3

Cylinders' position: In line

Oil capacity (L): 6.9

Cooling: Water

Alternator: Linz E1S13MD, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 2.8 at 75% of the load / 3.8 at 100% of the load

Running time (h): 18 at 75% of the load / 13.5 at 100% of the load

Acoustic power: 93 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 430

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar