



# GENERATOR WITH MANUAL PANEL 1000lt TANK

**Product price:**

**12.025,00 € tax excluded**

## **Product description:**

Single/three-phase 30KVA super-silenced genset with manual panel 1000lt tank

30KVA single/three-phase genset with 1500 rpm diesel-powered Perkins engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and with an internal lining of high noise-abatement material that makes it supersilenced.

The genset consists of a Stamford, Mecc Alte or Marelli Motori alternator, self-excited, brushless and with AVR voltage regulator. The genset has an electric start with a low fuel consumption battery, consuming only 178 litres/hour at 75% load. For greater convenience of use the tank.

This genset is perfect for use outdoors, such as on construction sites.

The genset is part of the Industrial range and is characterised by versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

## **Technical characteristics of the genset**

Phase type: Single-phase / Three-phase

Maximum three-phase power: 26.4 KW / 33 KVA

Three-phase continuous power: 24 KW / 30 KVA

Single-phase maximum power: 8.8 KW / 11 KVA

Single-phase continuous use power: 8 KW / 10 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1103A-33G

Motor speed: 1500 rpm



Starting: Electric  
Consumption: 5.6 Lt/h at 75% load  
Length: 2000 mm  
Width: 850 mm  
Height: 1280 mm  
Weight: 930 Kg  
Supersilenced  
AVR  
Emission category: EU STAGE 0  
Autonomy: 178 h

If you are looking for a product such as a Generator Set then you can browse the entire range of generators or others in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 8.8  
Continuous power single phase (KW): 8  
Maximum power single phase (KVA): 11  
Continuous power single phase (KVA): 10  
Maximum power three phase (KW): 26.4  
Continuous power three phase (KW): 24  
Maximum power three phase (KVA): 33  
Continuous power three phase (KVA): 30  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration:  
Engine: Perkins 1103A-33G  
Emissions Regulations: Stationary Use  
Engine rpm (rpm): 1500  
Speed governor: Mechanical  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 3300  
Number cylinders: 3  
Cooling: Water  
Alternator: Brushless  
Poles: 4  
Protection degree: IP44  
Bore x stroke (mm): 105 x 127



---

Fuel tank capacity (L): 1000  
Consumption (L/h): 5.6  
Running time (h): 178  
Acoustic pressure: 69 dB(A) at 7 m  
Length (mm): 2000  
Width (mm): 850  
Height (mm): 1280  
Dry weight (Kg): 930  
AVR: Yes  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Perkins

