



GENERATOR WITH MANUAL PANEL 1000lt TANK

Product price:

12.025,00 € tax excluded

Product description:

Single/three-phase 30KVA super-silenced genset with manual panel 1000lt tank

30KVA single/three-phase genset with 1500 rpm diesel-powered Perkins engine, compact and easy to use, mounted on a fixed base. This generator is equipped with a soundproofed cabin made of structural steel plate, weatherproofed and with an internal lining of high noise-abatement material that makes it supersilenced.

The genset consists of a Stamford, Mecc Alte or Marelli Motori alternator, self-excited, brushless and with AVR voltage regulator. The genset has an electric start with a low fuel consumption battery, consuming only 178 litres/hour at 75% load. For greater convenience of use the tank.

This genset is perfect for use outdoors, such as on construction sites.

The genset is part of the Industrial range and is characterised by versatility for installation in urban environments such as shops or shopping centres, for the telecommunications environment, for military applications and much more.

Technical characteristics of the genset

Phase type: Single-phase / Three-phase

Maximum three-phase power: 26.4 KW / 33 KVA

Three-phase continuous power: 24 KW / 30 KVA

Single-phase maximum power: 8.8 KW / 11 KVA

Single-phase continuous use power: 8 KW / 10 KVA

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: PERKINS 1103A-33G

Motor speed: 1500 rpm



Starting: Electric
Consumption: 5.6 Lt/h at 75% load
Length: 2000 mm
Width: 850 mm
Height: 1280 mm
Weight: 930 Kg
Supersilenced
AVR
Emission category: EU STAGE 0
Autonomy: 178 h

If you are looking for a product such as a Generator Set then you can browse the entire range of generators or others in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 8.8
Continuous power single phase (KW): 8
Maximum power single phase (KVA): 11
Continuous power single phase (KVA): 10
Maximum power three phase (KW): 26.4
Continuous power three phase (KW): 24
Maximum power three phase (KVA): 33
Continuous power three phase (KVA): 30
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Sockets configuration:
Engine: Perkins 1103A-33G
Emissions Regulations: Stationary Use
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 3300
Number cylinders: 3
Cooling: Water
Alternator: Brushless
Poles: 4
Protection degree: IP44
Bore x stroke (mm): 105 x 127



Fuel tank capacity (L): 1000
Consumption (L/h): 5.6
Running time (h): 178
Acoustic pressure: 69 dB(A) at 7 m
Length (mm): 2000
Width (mm): 850
Height (mm): 1280
Dry weight (Kg): 930
AVR: Yes
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Perkins

