

# GENSET MG 50 I-SY - SINGLE-PHASE/THREE-PHASE GENERATOR 44 KVA AVR Stage 0



**Product price:**

**11.715,00 € tax excluded**

## **Product description:**

GENSET MG 50 I-SY - SINGLE-PHASE-THREE-PHASE ELECTRIC GENERATOR 44 KVA AVR Stage 0

The three-phase 44 KVA diesel generator is the ideal solution for those who need a reliable and powerful energy source in professional or domestic contexts.

## **Main features GENSET MG 50 I-SY:**

High power:

Three-phase maximum power: 44 KVA (35.2 kW)

Three-phase continuous power: 39.6 KVA (31.68 kW)

Single-phase maximum power: 14.6 KVA (11.68 kW)

Yanmar 4TNV98T engine (STAGE 0): Reliable, high-performance, liquid-cooled 4-cylinder diesel engine complying with STAGE 0 emission standards.

Electric start: Quick and easy starting with key.

Efficient consumption: Low fuel consumption (8.1 Lt/h) for optimum range.

Super silent: Soundproof design for silent operation.

Robust construction: Compact and robust design for easy transport and storage



## Technical specifications GENSET MG 50 I-SY

Maximum three-phase power: 44 KVA  
Maximum three-phase power: 35.2 KW  
Three-phase continuous use power: 39.6 KVA  
Three-phase continuous use power: 31.68 KW  
Single-phase maximum power: 14.6 KVA  
Maximum power single-phase: 11.68 KW  
Fuel: Diesel  
Voltage: 230/400 V  
Frequency: 50 Hz  
Engine: Yanmar 4TNV98T (STAGE 0)  
Starter: Electric  
Consumption: 8.1 Lt/h  
Tank: 40 lt  
Length: 1900 mm  
Width: 910 mm  
Height: 1100 mm  
Weight: 735 Kg  
Super silenced  
AVR

if you are looking for a generator set such as GENSET MG 50 I-SY or with similar characteristics? [CLICK HERE](#).

Images and technical data are not binding.

### Product features:

Phase: Single phase / Three phase  
Maximum power single phase (KW): 11.68  
Maximum power single phase (KVA): 14.6  
Maximum power three phase (KW): 35.2  
Continuous power three phase (KW): 31.68  
Maximum power three phase (KVA): 44  
Continuous power three phase (KVA): 39.6  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 63A CEE - 1 x 400V 32A CEE - 1 x 230V 32A CEE - 230V 16A CEE  
Engine: Yanmar 4TNV98T, 4 stroke  
Emissions Regulations: Stage 0



---

Engine rpm (rpm): 1500  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 3319  
Number cylinders: 4  
Cooling: Water  
Alternator: Synchronous  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 40  
Consumption (L/h): 8.1  
Running time (h): 4.94  
Acoustic power: 95 dB(A)  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 1900  
Width (mm): 910  
Height (mm): 1100  
Dry weight (Kg): 735  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Yanmar