



# PRAMAC GBW22P 20KVA THREE-PHASE SUPERSILENT AUTOMATIC PANEL GENERATOR

Product price:

**10.822,50 € tax excluded**

## Product description:

PRAMAC GBW22P 20KVA THREE-PHASE SUPERSILENT AUTOMATIC PANEL GENERATOR

The PRAMAC GBW22P three-phase generator is equipped with a Perkins 404A-22G1 diesel engine and is capable of delivering a maximum power of 20 KVA.

The PRAMAC GBW22P generator comes with electric, manual, or automatic starting options using a 12V battery. It features a **Deep Sea controller** that displays all electrical parameters of the engine and generator, operational functions, generator status, and allows comprehensive management of the generator. It also displays any potential system errors or alarms.

The PRAMAC GBW22P generator ensures efficient and quiet operation, powered by the Perkins 404A-22G1 engine, capable of delivering a maximum power of 20 KVA.

## PREPARATION FOR AUTOMATIC START PANEL (ATS)

The generator is prepared for use with an Automatic Start Panel (ATS), which automatically starts the generator in case of a power outage. This feature ensures uninterrupted operation and data retention during power interruptions.

## Standard Equipment:

LINZ alternators with Compound regulation  
Reversible hood with gas springs  
Residential muffler

Lifting hook  
Forcible base with wheels  
Engine and battery fluids  
Oil extraction pipe

#### TECHNICAL SPECIFICATIONS PRAMAC GBW22P

Phase Type: Three-Phase  
Continuous Use Power: 19.78 KVA / 15.82 KW  
Maximum Power: 21.82 KVA / 17.46 KW  
Engine: Perkins 404A-22G1  
Emissions Regulation: Stage 0  
Engine Speed: 1500 rpm  
Starting: Electric / Automatic  
Fuel: Diesel  
Voltage at Terminals: 400 V  
Frequency: 50 Hz  
Voltage Regulator: Compoud  
Socket Panel: 1 x 400V CEE 32A | Terminal block  
Tank Capacity: 51 l  
Consumption at 75% Load: 3.98 l/h  
Autonomy at 75% Load: 12.81 h  
Sound Pressure: 66 dB(A) @ 7 m  
Length: 1645 mm  
Width: 870 mm  
Height: 1072 mm  
Dry Weight: 565 Kg

Looking for a generator with different technical specifications? Check out the dedicated section for PRAMAC generators or other specialized brands.

Images and technical data are not binding.

#### Product features:

Phase: Three phase  
Maximum power three phase (KW): 17.46  
Continuous power three phase (KW): 15.42  
Maximum power three phase (KVA): 21.82  
Continuous power three phase (KVA): 19.78  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 400

---

Sockets configuration: 1 x 400V CEE 32A | Terminal block  
Engine: Perkins 404D-22G  
Emissions Regulations: Stage 0  
Speed governor: Mechanical  
Starting system: Electric / Automatic  
Engine capacity (cm<sup>3</sup>): 2216  
Number cylinders: 4  
Cylinders' position: In line  
Oil capacity (L): 10.6  
Cooling: Water  
Alternator: Linz E1S13MF, with brushes  
Poles: 4  
Fuel tank capacity (L): 51  
Consumption (L/h): 4 at 75% of the load / 5.3 at 100% of the load  
Running time (h): 12.8 at 75% of the load / 9.7 at 100% of the load  
Acoustic power: 95 dB(A)  
Acoustic pressure: 66 dB(A) at 7 m  
Length (mm): 1645  
Width (mm): 870  
Height (mm): 1072  
Dry weight (Kg): 565  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : Optional  
Voltage regulator: Compound  
Engine manufacturer: Perkins