



PRAMAC GBW22Y GENSET WITH MANUAL CONTROL PANEL



Product price:

8.190,00 € tax excluded

Product description:

PRAMAC GBW22Y MCP Three-phase 15.4 KW Super Silent Generator

The PRAMAC GBW22Y three-phase generator with 15.4 KW power has a diesel engine running at 1500 rpm. The PRAMAC GBW22Y generator is equipped with an electric start. The alternator of the PRAMAC GBW22Y generator has brushes with a compound voltage regulator. The Yanmar diesel engine makes the GBW22Y generator highly reliable as it is built and designed using top-quality materials.

Thanks to its casing, this generator is super silent. Additionally, it is easy to transport, install, and position thanks to its compact size, making this model ideal for emergency power, construction, mobile workshops, and industrial applications. The PRAMAC GBW22Y three-phase generator is suitable for outdoor use on construction sites or for small professional outdoor jobs.

Technical specifications of the PRAMAC GBW22Y Three-phase generator:

- Maximum Three-phase Power: 15.48 KW
- Continuous Three-phase Power: 14.1 KW
- Fuel: Diesel
- Voltage: 400 V
- Frequency: 50 Hz
- Engine: Yanmar 4TNV88-BIPGE STAGE V
- Start: Electric
- Consumption: 5 Lt/h at 100% load
- Length: 1645 mm
- Width: 870 mm
- Height: 1072 mm
- Weight: 560 Kg
- Compound



**Sockets:**

- N.1 3P+N+T CEE 400V 32A
- N.1 3P+N+T CEE 400V 16A
- N.2 2P+T CEE 230V 16A
- N.1 230V 16A SCHUKO

The PRAMAC GBW22Y power generator is a professional diesel generator developed by Pramac with the characteristics and equipment necessary to obtain a superior class product. The PRAMAC GBW22Y power generator, with its low noise level, is the ideal generator for use in residential areas or during non-working hours.

The GBW22Y generator is equipped with a reliable diesel engine, top-quality components, and complete instrumentation.

If you are looking for a generator like the GBW22Y three-phase power generator, we recommend browsing our catalog of terrestrial generators to find the one that best suits your needs.

Images and technical data are non-binding.

Product features:

Phase: Three phase

Maximum power three phase (KW): 15.48

Continuous power three phase (KW): 14.1

Maximum power three phase (KVA): 19.35

Continuous power three phase (KVA): 17.63

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE - 1 x 400V 16A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system: Elettrico

Engine capacity (cm³): 2190

Number cylinders: 4

Cylinders' position: In line



Oil capacity (L): 7.4

Cooling: Water

Alternator: Linz E1S13MF, with brushes

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h): 3.8 at 75% of the load / 5 at 100% of the load

Running time (h): 13.4 at 75% of the load / 10.1 at 100% of the load

Acoustic power: 93 dB(A)

Acoustic pressure: 64 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg): 560

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : No

Voltage regulator: Compound

Engine manufacturer: Yanmar