

# GYS MULTIWELD 400T WELDING MIG - MAG - MMA Inverter



**Product price:**

**1.546,00 € tax excluded**

## **Product description:**

GYS MULTIWELD 400T MIG - MAG - MMA Inverter Welding Machine

GYS MULTIWELD 400T MIG - MAG - MMA Inverter Welding Machine: Maximum Power and Versatility for Your Welding Needs

The GYS MULTIWELD 400T is a state-of-the-art three-phase power source that offers maximum power and versatility for your welding needs. Combining MIG/MAG, flux cored wire and MMA processes in one robust machine, the MULTIWELD 400T guarantees flawless results on a variety of materials, including aluminium. Featuring an intuitive interface, a high-performance wire feed system and advanced technologies, this inverter is the ideal choice for professionals and experienced hobbyists alike.

## **Key features:**

MIG/MAG: steel and stainless steel wire (Ø 0.6 - 1.6 mm), aluminium wire (Ø 0.8 - 1.6 mm), flux cored wire (reverse polarity: Ø 0.9 - 1.2 mm)

MMA: basic and rutile electrodes (up to Ø 5 mm), arc gouging with carbon electrode (up to Ø 6 mm)

## **Welding functions:**

Choice of torch trigger behaviour: 2T or 4T for greater customisation of the welding process.

3 settings for precise control: pre-gas, wire feed and post-gas duration (0, 0.5 or 1 second).

Welding aid: the table on the front panel helps to easily set the tension and wire diameter according to the thickness of the material to be welded.



### **Interface and controls:**

Intuitive digital screens for easy reading and adjustment of settings, even in low light.

Simple interface with buttons and knobs suitable for grooved hands for convenient and safe operation.

### **Wire feed system:**

Compatible wire spools: Ø 200 / 300 mm

Powerful and precise 4-roller wire feeder for efficient unwinding even of Ø 1.6 mm wire.

Other features:

European torch connector for quick and safe assembly/disassembly.

Pre-installed socket (36 V AC - 4.2 A) for welding gas heater under pure CO<sub>2</sub> (heater not included).

Compatible with US (type A) and EURO (types C/E/F) electrical sockets.

Robust and portable thanks to reinforced trolley and sturdy wheels for stability and manoeuvrability.

Holder for 10 m<sup>3</sup> gas cylinder.

Door and space for accessories for organisation and convenience.

### **Technical characteristics:**

Supply voltage: 400 V

Mains frequency: 50/60 Hz

Adjustable welding current (MIG & MAG):

400V - I2 MMA: 40 - 400A

400V - I2 MIG: 40 - 400A

Reference standards:

EN 60974-1 (40°C)

Weight: 64 Kg

Degree of protection: IP 21

Product dimensions: 910 x 930 x 550 mm

Power combined with generator: 00 Kwa

MACHINE THICKNESS

GAS in 400V: 0.6 - 1.6 øm



NO GAS in 400v: 0.9 - 1.2 øm  
Electronic Control: Automatic  
Vacuum Voltage: 70 V

Looking for a portable welding machine with different features? Here you can find the whole range of HELVI or other specialized brands

Images and technical data are not binding and may be subject to revision by the supplier

**Product features:**

Phase: Three phase

Frequency (Hz): 50 / 60

Voltage (V): 400

Protection degree: IP21

Product dimensions (mm): 910 x 930 x 550

No-load voltage (V): 70

Regulation current (A): 400V I2 MMA: 40 - 400 / I2 MIG: 40 - 400

Type of welding: MMA / MIG / MAG

Weight (Kg): 64

EN 60974-1 (40°C): MIG / MAG IA (60%): 300 A / MMA - 100%: 240A