

PRAMAC GBW45Y APERTO CON QUADRO COMANDO AUTOMATICO



Product description:

Motore Diesel. Raffreddamento ad acqua. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica. Quadro manuale MCP fornito di serie con 5 prese

Product features:

Phase: Three phase

Maximum power three phase (KW): 36.68

Continuous power three phase (KW): 34.82

Maximum power three phase (KVA): 45.85

Continuous power three phase (KVA): 43.52

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 32A 3P+N+T CEE

Engine: Yanmar 4TNV98T-GPGE, turbocharged

Emissions Regulations: Stage 2

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3319

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10.5

Cooling: Water

Alternator: Mecc Alte ECO/P32-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 51



Consumption (L/h): 8.2 at 75% of the load / 10.9 at 100% of the load
Running time (h): 6.2 at 75% of the load / 4.7 at 100% of the load
Length (mm): 2000
Width (mm): 920
Height (mm): 1100
Dry weight (Kg): 611
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Yanmar

