



# SATEPA UV Steriliser UVC30A - Adaptor with Plug-in Power Supply

**Product price:**

**344,00 € tax excluded**

## **Product description:**

SATEPA UV Steriliser UVC30A - Adaptor with Plug-in Power Supply

The UVC30A UV Steriliser - Adaptor with Plug-in Power Supply from SATEPA is the ideal solution for efficient and safe water debacterisation in a variety of applications. Thanks to its advanced technology and compact design, this device is perfect for use in domestic, commercial and industrial environments.

## **Key features:**

**Proven efficacy:** Harnesses the power of UV-C rays with a wavelength of 254 nm to eliminate bacteria, viruses and other microorganisms from water, ensuring deep and complete disinfection.

**Low-pressure mercury vapour lamp:** Offers a long life of up to 9,000 hours and high effectiveness in water debacterialisation.

**High-quality quartz sheath:** Protects the lamp and ensures optimal UV-C transmission for uniform debacterisation.

**Plug-in power supply:** Easy to install and use, allowing the UV steriliser to be plugged into any standard electrical outlet.

**Lamp monitor with red/green LED:** Indicates lamp status, facilitating preventive maintenance.

**SCHUKO/EU plug:** Compatible with the most common electrical sockets in Europe.

**Compact and versatile design:** Its small dimensions (200 x 160 x 90 mm) make it ideal for installation in tight spaces.

**High adaptability:** Can be installed vertically or horizontally to adapt to any location.



Standard hydraulic connections: ¾" male threaded for easy connection to existing piping.

Maximum pressure of 10 Bar: Suitable for a wide range of applications.

**Technical characteristics:**

Maximum flow rate: 1.5 m<sup>3</sup>/h - 1500 l/hr - 6.60 GPM @ 30,000 µWsec/cm<sup>2</sup> 1.2 m<sup>3</sup>/h - 1200 l/hr - 5.28 GPM @ 40,000 µWsec/cm<sup>2</sup>

Lamp: 1x30W, lifetime 9,000 hr

Frame size: 65 x 12 mm H=60mm

Degree of protection: IP 54

Absorption: 40 Watt

Power supply voltage: 230 Vac ± 10% @ 50/60 Hz

Chamber dimensions: Total H 530 mm ; Ø 60.30 mm

Working position: Vertical / horizontal

Hydraulic connection: ¾" male threaded

Maximum pressure: 10 Bar standard

Product dimensions: 450 x 60.30 mm

I/O: ¾"

Lamp: 1 x 30W

Looking for a UV steriliser with different features? [Click HERE.](#)

Images and technical data purely indicative.

**Product features:**

Frequency (Hz): 50 / 60

Protection degree: IP54

Power cable length (m): 1,5 m

Pressure (bars): 10

Product dimensions (mm): 120 x 65 x 45

Lamps: 1 x 30W

Power consumption (W): 40

Capacity (Lt/h): 1200 - 1500

Output voltage (VAC): 90 - 240

Reactor Dimensions: H total: 450 mm - Ø 60,30 mm

Form: C-shaped tube

job position: Vertical / Horizontal

Power supply: High-efficiency electronic ballast

---

lamp control: Lamp monitoring with red/green LED  
electrical connection: SCHUKO/EU plug or feed-through cable