

Generator Set Three-phase Silenced Automatic 66KVA STAGE II



Product price:

13.417,00 € tax excluded

Product description:

Generator Set Three-phase Silenced Automatic 66KVA STAGE II

presents the Automatic Automatic Silenced Three-Phase Generating Set 66KVA, a concentrate of power and silence to meet your electricity needs reliably and safely.

Ideal for:

Construction sites: Powering machinery and equipment even in the absence of a mains power supply.

Companies and industries: Ensures continuity of production in the event of a blackout.

Events and exhibitions: Provides power for lighting, audio-video systems and other devices.

Homes and houses: Provides emergency backup in the event of power outages.

Key features:

High power: 66 KVA in LTP and 60 KVA in PRP to cope with demanding loads.

DEUTZ BF4M2011C engine: Reliable, high-performance diesel engine, ensures quiet, continuous operation.

Electric start: Quick and easy start for immediate use.

Tank capacity: 120 l: Extended operating time for greater flexibility.

Noise level: 66 db(A): Quiet operation that makes it suitable for noise-sensitive environments.



Enclosure type: T62: Robust and resistant, protects the genset from the elements.

Advantages:

Proven reliability: Designed and manufactured with high-quality components to ensure long-lasting operation.

Power and performance

High power and performance: Meets the highest load demands, even under severe working conditions.

Exceptionally quiet: The diesel engine and soundproofed enclosure minimise noise, making it ideal even in noise-sensitive environments.

Ease of use: Electric start and intuitive control panel for simple and immediate operation.

Versatility: Suitable for a wide range of applications, from domestic to industrial.

If you are looking for a product similar to Three-phase Silenced Automatic Generator Set

Technical characteristics:

Generator set power in LTP: 66 KVA

Power of genset in PRP: 60 KVA

Generator set power in LTP: 53 KW

Generator set power in PRP: 48 KW

Fuel: Diesel

Voltage: 230/400 V

Motor: DEUTZ BF4M2011C

Degree of protection: IP42

Starter: Electric

Tank capacity: 120 lt.

Dimensions (mm): 2260x1000x1420

Weight: 1170 Kg

Noise level: 66 db(A)

Enclosure type: T62

Alternator: MECC ALTE ECP32 2M/4
STAGE II

Displacement: 3108 cc

Specific consumption at 75% load: 10.1 L/H

Switching quander for GET 66KVA STAGE II

If you are looking for a product similar to Three-phase Silenced Automatic Generator Set click [HERE](#).



The image is purely indicative.

Product features:

Phase: Three phase

Maximum power three phase (KW): 52.8

Continuous power three phase (KW): 48

Maximum power three phase (KVA): 66

Continuous power three phase (KVA): 60

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: FPT N45SM1A

Emissions Regulations: Stage 2

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3108

Number cylinders: 4

Poles: 4

Protection degree: IP42

Product dimensions (mm): 2260x1000x1420

Fuel tank capacity (L): 120

Consumption (L/h): 10

Acoustic pressure: 66 dB(A)

Dry weight (Kg): 1170

Silenced: Yes

Super silenced: Yes

ATS Switch device : Optional