



SATEPA UV Steriliser MONO UVC40D3 - Display UV CUBE

Product price:

304,00 € tax excluded

Product description:

SATEPA UV Sterilizer MONO UVC30D3 - Display UV CUBE

SATEPA UV Sterilizer UVC40D3 - UV CUBE Display

SATEPA UV Sterilizer UVC40D3 - Display UV CUBE: Product Description.

SATEPA UV Sterilizer UVC40D3 - Display UV CUBE is a device designed for disinfection of drinking and industrial water using UV-C radiation.

Its effectiveness is based on the emission of UV-C radiation at a wavelength of 254 nm, which can inactivate pathogenic microorganisms such as bacteria, viruses and protozoa.

Main features:

Maximum flow rate:

2.8 m³/h (2800 l/h) at 30,000 μWsec/cm²

2.4 m³/h (2400 l/h) at 40,000 μWsec/cm²

Lamps: 1x40W, lasting up to 9,000 hours

Ballast dimensions: 928 mm (total height) x Ø 60.30 mm

Finish: "C" tube

Working position: Vertical or horizontal

Hydraulic connections: 1" male threaded

Maximum pressure: 10 Bar standard

Materials: AISI 304 (AISI 316 optional)

UV3:

Square dimensions: 180 x 180 x 90 mm

Display: white/blue backlit LCD with 2x8 characters

Lamp control: Single lamp management with end-of-life alarm via LED/relay



**Counts:**

Total lamp life hour counter
Partial lamp life hour counter (resettable)
Lamp change count

Commands:

Stand By command with "OK" button
Remote ON/OFF command
Operating modes:
Lamp on with water flow
Solenoid valve closing in case of lamp off
Customizations: Customizable input signal

Alarms:

Dry contact alarm relay 1 A @ 30Vdc; 0.250 A @ 230 Vac
Power alarm relay 1A @ 30Vdc; 0.250A @ 230 Vac
IP rating: IP 54 (IP 65 optional)
Power consumption: 40 watts
Power supply: 230 Vac \pm 10% @ 50/60 Hz

Specifications:

Maximum flow rate: 2.8 m³/Hr - 2800 l/hr - 12.30 GPM @ 30,000 μ Wsec/cm²
2.4 m³/Hr - 2400 l/hr - 10.60 GPM @ 40,000 μ Wsec/cm²
Panel size: 180 x 180 x 90 mm
Display: 2x8 characters white/blue backlit LCD display
Lamp control: Single lamp management with end of lamp life alarm through led/relay
Counts: Total lamp life hour counter
Resettable partial lamp life hour counter
Lamp change counting
Commands: Stand By command with "OK" button
Remote ON/OFF command
Lamp on mode with water flow
Solenoid valve closing mode in case of lamp off
Customizations: Customizable input signal
Alarms: Dry contact alarm relay 1 A @ 30Vdc; 0.250 A @ 230 Vac
Power alarm relay 1A @ 30Vdc; 0.250A @ 230 Vac
IP rating: IP 54 (IP 65 optional)
Power consumption: 40 watts
Power supply: 230 Vac \pm 10% @ 50/60 Hz
Product dimensions: 928 x 60.30 mm

Advantages:

High disinfection effectiveness: Eliminates pathogenic microorganisms
Safe and environmentally friendly: Does not use chemicals harmful to the environment
Low energy consumption: Reduces operating costs
Low maintenance: Easy to install and use
Versatility: Suitable for a wide range of applications

Looking for a UV steriliser with different features? [Click HERE.](#)

Images and technical data purely indicative.

Product features:

Frequency (Hz): 50 / 60

Protection degree: IP54

Pressure (bars): 10

Product dimensions (mm): 928 x 60,30

Lamps: 1 x 40 W

Power consumption (W): 30

Capacity (Lt/h): 2800

Output voltage (VAC): 230

Reactor Dimensions: H total: 928 mm - Ø 60,30 mm

Form: C-shaped tube

job position: Vertical / Horizontal

lamp control: Gestione singola lampada con allarme fine vita lampada attraverso led/relè