



SATEPA UV Steriliser MONO UVC80D3 - Display LCD

Product price:

766,00 € tax excluded

Product description:

SATEPA UV Steriliser MULTI UVC80D3 - DISPLAY LCD

SATEPA UV MULTI Sterilizer UVC80D3 - LCD Display

UV sterilizer suitable for water debacterialization by UV-C radiation with wavelength of 254nm.

Equipped with 2 low-pressure mercury vapor lamps of 80W electrical power, enclosed in quartz sheaths

purest, driven by high-efficiency electronic power supplies and digital LCD display control unit with sensor of

irradiance and optional temperature with corresponding tube arrangement.

Key Features *SATEPA UV MULTI Sterilizer UVC80D3:*

Flow rate:

Maximum: 12 m³/hr - 12000 l/hr - 52.8 GPM @ 30,000 μWsec/cm²

Reduced: 9 m³/hr - 9000 l/hr - 39.6 GPM @ 40,000 μWsec/cm²

Lamps:

2x80W

Lifetime: 9,000 hours

SATEPA Reactor UV MULTI Sterilizer UVC80D3:

Dimensions: Total H: 928 mm - Ø 114 mm

Form Factor: "Z" tube

Working position: Vertical

Hydraulic connections:





1½" male threaded (flange optional)
½" water discharge
Maximum pressure: 10 Bar standard
Material: AISI 304 (AISI 316 optional)

SATEPA MULTI UVC80D3 UV sterilizer control panel:

Dimensions: 180 x 180 x 90 mm
Display: white/blue backlit LCD 2x8 characters
Functionality:
Single lamp management
End of lamp life alarm (LED/relay)

SATEPA UV MULTI UVC80D3 Counts:

Total plant life hour counter
Partial life hour count (resettable)
Lamp change count
Commands:
Stand By with "OK" button
Remote ON/OFF

Technical features SATEPA UV MULTI sterilizer UVC80D3 - LCD display:

Maximum flow rate: 2.8 m³/Hr - 2800 l/hr - 12.30 GPM @ 30,000 µWsec/cm² 2.4 m³/Hr - 2400 l/hr - 10.60 GPM @ 40,000 µWsec/cm²
Panel size: 180 x 180 x 90 mm
Display: 2x8 characters white/blue backlit LCD display
Control: Single lamp management with end-of-life alarm through led/relay
Counts: Total lamp life hour counter
Resettable partial life hours counter
Controls: Stand By command with "OK" button
SATEPA Remote ON/OFF Command
Lamp on mode with water flow
Solenoid valve closing mode when off
Customizations: Customizable input signal
Alarms: Dry contact alarm relay 1 A @ 30Vdc; 0.250 A @ 230 Vac
Power alarm relay 1A @ 30Vdc; 0.250A @ 230 Vac
IP rating: IP 54 (IP 65 optional)
Power consumption: 40 watts
Power supply: 230 Vac ± 10% @ 50/60 Hz
Product dimensions: 928 x 60.30 mm
Advantages SATEPA UV MULTI Sterilizer UVC80D3 - LCD Display:
High disinfection effectiveness: Eliminates pathogenic microorganisms





Safe and environmentally friendly: Does not use chemicals harmful to the environment
Low energy consumption: Reduces operating costs
Low maintenance: Easy to install and use
Versatility: Suitable for a wide range of applications

Looking for a *SATEPA UV MULTI Sterilizer UVC80D3* with different features? Click [HERE](#).

Images and technical data purely indicative.

Product features:

Frequency (Hz): 50 / 60

Protection degree: IP54

Pressure (bars): 10

Product dimensions (mm): 928 x 114

Lamps: 2 x 80 W

Power consumption (W): 160 W

Capacity (Lt/h): 9000 - 12000

Output voltage (VAC): 230

Reactor Dimensions: H totale: 928 mm - Ø 114 mm

Form: Z-pipe

job position: Vertical

lamp control: Gestione singola lampada con allarme fine vita lampada attraverso led/relè

