



SATEPA UV Steriliser MULTI UVC390D - Display LCD

Product price:

1.650,00 € tax excluded

Product description:

SATEPA UV Steriliser MULTI UVC390D - Display LCD

SATEPA UV Multi Sterilizer UVC390D- LCD Display: Purity and Safety

SATEPA's UV Multi UVC390D- LCD Display Sterilizer is the ideal solution to ensure the debatinization of large volumes of water efficiently and safely in a variety of applications. With its 6 low-pressure mercury vapor lamps and advanced technology, this device can eliminate bacteria, viruses and other microorganisms from water, ensuring deep and complete disinfection.

Key Features *SATEPA UV Sterilizer Multi UVC390D - LCD Display:*

Proven Effectiveness: Uses the power of UV-C rays with a wavelength of 254 nm to eliminate bacteria, viruses and other microorganisms.

6 low-pressure mercury vapor lamps: Provides high sterilization power and long life of up to 9,000 hours.

Ultra-pure quartz sheaths: They protect the lamps and ensure optimal UV-C transmission for uniform debatinization.

High-efficiency electronic power supply: Reduces energy consumption and ensures reliable operation.

Digital control unit with LCD display: Allows you to monitor the operating status of the sterilizer, display irradiance and temperature data, and set operating parameters.

Optional irradiance and temperature sensor: Provides precise control of UV-C intensity and water temperature for optimal debatinization.





Advantages SATEPA Sterilizer UV Multi UVC390D - LCD Display:

SATEPA Pure and Safe Water: Eliminates harmful microorganisms from water, ensuring safe drinking and optimal hygiene for large volumes.

Health protection: Prevents the spread of diseases related to contaminated water.

Reduced chlorine use: Allows the use of chlorine and other chemicals for water disinfection to be decreased or eliminated, promoting a

healthier and more sustainable environment.

SATEPA Energy Efficiency: High-efficiency electronic ballast ensures low power consumption.

Easy Maintenance: Lamps are easily replaced, and the monitoring system makes it easy to manage the UV sterilizer.

Technical Specifications SATEPA UV Sterilizer Multi UVC390D - LCD Display:

Maximum: 35 m³/h - 35000 l/m - 154.00 GPM @ 30,000 μWsec/cm²

Reduced: 28 m³/h - 28000 l/m - 123.30 GPM @ 40,000 μWsec/cm²

Number: 6

Power: 80W each

Service life: 9,000 hours

Dimensions: Total H: 933 mm - Ø 168 mm

Form Factor: "Z" tube

Working position: Vertical

Inlet: 2½" male threaded (flange optional)

Water outlet: ½"

Maximum pressure: 10 Bar standard

Material: AISI 304 (AISI 316 optional)

Panel size: 240 x 310 x 125 mm

Display: white/blue backlit LCD 2x8 characters

End of lamp life alarm through LED/relay

Total plant life hour counter

Partial life hour counter (resettable)

Lamp change count

Stand By command with "OK" button

Remote ON/OFF command (e.g. flowmeter)

Solenoid valve control with 230 Vac power relay in exchange @ 0.250 A

Dry contact alarm relay 1 A @ 30Vdc; 0.250 A @ 230 Vac

IP rating: IP 54

Power consumption: 480 watts





Power supply: 230 Vac \pm 10% @ 50/60 Hz

Commands: Looking for a SATEPA UV steriliser with different features? Click [HERE](#).

Images and technical data purely indicative.

Product features:

Frequency (Hz): 50 / 60

Protection degree: IP54

Pressure (bars): 10

Lamps: 6 x 80 W

Power consumption (W): 480

Capacity (Lt/h): 18000 - 23000

Output voltage (VAC): 230

Reactor Dimensions: H total: 933 mm - \varnothing 168 mm

Form: Z-pipe

job position: Vertical

lamp control: Gestione singola lampada con allarme fine vita lampada attraverso led/relè

