



PRAMAC GSL30D COFANATO CON QUADRO COMANDO MANUALE

Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Product features:

Phase: Three phase

Maximum power three phase (KW): 25.55

Continuous power three phase (KW): 24.31

Maximum power three phase (KVA): 31.94

Continuous power three phase (KVA): 30.39

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 63A 3P+N+T - 1 x 400V 32A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Deutz AG F4M2011, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 68



Consumption (L/h): 5.7 at 75% of the load / 8 at 100% of the load
Running time (h): 11.9 at 75% of the load / 8.4 at 100% of the load
Acoustic power: 89 dB(A)
Acoustic pressure: 60 dB(A) at 7 m
Length (mm): 2005
Width (mm): 948
Height (mm): 1308
Dry weight (Kg): 760
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Deutz

