



# PRAMAC GSL30D COFANATO CON QUADRO COMANDO MANUALE

## Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

## Product features:

Phase: Three phase

Maximum power three phase (KW): 25.55

Continuous power three phase (KW): 24.31

Maximum power three phase (KVA): 31.94

Continuous power three phase (KVA): 30.39

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 63A 3P+N+T - 1 x 400V 32A 3P+N+T CEE - 2 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Deutz AG F4M2011, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 68



---

Consumption (L/h): 5.7 at 75% of the load / 8 at 100% of the load  
Running time (h): 11.9 at 75% of the load / 8.4 at 100% of the load  
Acoustic power: 89 dB(A)  
Acoustic pressure: 60 dB(A) at 7 m  
Length (mm): 2005  
Width (mm): 948  
Height (mm): 1308  
Dry weight (Kg): 760  
Silenced: Yes  
Super silenced: Yes  
Product type: Generator  
ATS Switch device : No  
Voltage regulator: AVR  
Engine manufacturer: Deutz

