

# PRAMAC GSL30D COFANATO CON QUADRO COMANDO AUTOMATICO



## Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

## Product features:

Phase: Three phase

Maximum power three phase (KW): 25.55

Continuous power three phase (KW): 24.31

Maximum power three phase (KVA): 31.94

Continuous power three phase (KVA): 30.39

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Sockets configuration: 1 x 400V 63A 3P+N+T CEE

Engine: Deutz AG F4M2011, naturally aspirated

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECP28-VL/4, brushless

Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 5.7 at 75% of the load / 8 at 100% of the load



Running time (h): 11.9 at 75% of the load / 8.4 at 100% of the load

Acoustic power: 89 dB(A)

Acoustic pressure: 60 dB(A) at 7 m

Length (mm): 2005

Width (mm): 948

Height (mm): 1308

Dry weight (Kg): 760

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Deutz

