



# PRAMAC GSL42D

## Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

## Product features:

Phase: Three phase

Maximum power three phase (KW): 35.62

Continuous power three phase (KW): 33.85

Maximum power three phase (KVA): 44.52

Continuous power three phase (KVA): 42.31

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Deutz AG BF4M2011, turbo

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 91

Consumption (L/h): 8.1 at 75% of the load / 11.2 at 100% of the load

Running time (h): 11.3 at 75% of the load / 8.1 at 100% of the load

Length (mm): 1800



---

Width (mm): 750  
Height (mm): 1518  
Dry weight (Kg): 761  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Deutz