



PRAMAC GSL42D

Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Product features:

Phase: Three phase

Maximum power three phase (KW): 35.62

Continuous power three phase (KW): 33.85

Maximum power three phase (KVA): 44.52

Continuous power three phase (KVA): 42.31

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Deutz AG BF4M2011, turbo

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 91

Consumption (L/h): 8.1 at 75% of the load / 11.2 at 100% of the load

Running time (h): 11.3 at 75% of the load / 8.1 at 100% of the load

Length (mm): 1800



Width (mm): 750
Height (mm): 1518
Dry weight (Kg): 761
Silenced: No
Super silenced: No
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Deutz