



PRAMAC GSL65D COFANATO CON QUADRO COMANDO MANUALE



Product description:

Motore Diesel. Predisposto per Biodiesel. Raffreddamento ad olio con radiatore. Silenziatore industriale. Base forcabile con carrelli. Liquidi motore e batteria carica

Product features:

Phase: Three phase

Maximum power three phase (KW): 48.76

Continuous power three phase (KW): 46.23

Maximum power three phase (KVA): 60.95

Continuous power three phase (KVA): 57.79

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: Deutz AG BF4M2011C, turbo intercooled

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 3110

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 10

Cooling: Oil

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 9.9 at 75% of the load / 13.4 at 100% of the load

Running time (h): 21 at 75% of the load / 15.6 at 100% of the load



Acoustic power: 93 dB(A)
Acoustic pressure: 64 dB(A) at 7 m
Length (mm): 2285
Width (mm): 920
Height (mm): 1310
Dry weight (Kg): 981
Silenced: Yes
Super silenced: Yes
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Deutz