

# GENSET SILENCED 33 KVA



## Product description:

GENSET SILENCED 33 KVA

SILENCED GENERATOR 33 KVA: Power and Reliability at your fingertips

The SILENCED GENERATING UNIT 33 KVA is a powerful electric generator designed to provide reliable and silent emergency or continuous power. With a maximum output of 33 kVA and a Baudouin 4M06G35/5 diesel engine, this generator set is the ideal solution for a wide range of applications, both domestic and industrial.

## Key features:

**Powerful and reliable:** The Baudouin diesel engine ensures high performance and a long service life.

**Quiet:** Thanks to its soundproof housing, the noise level at 7 metres is only 70 dB(A), ensuring discrete operation.

**Versatile:** The 230V/400V output voltage and 50 Hz frequency make it compatible with most household appliances and equipment.

**Autonomy:** The 100-litre tank guarantees a long operating autonomy.

**Compact dimensions:** With its small size (2100x870x1165 mm), it can be easily transported and installed.

**Low emissions:** The engine complies with emission regulations, respecting the environment.

**Technical characteristics SILENCED ELECTROGEN GROUP 33 KVA:**

Type of phase: Three-phase  
Three-phase continuous power: 24 kW  
Three-phase continuous power: 30 kVA  
Maximum three-phase LTP power: 26.4 kW  
Maximum three-phase LTP power: 33 kVA  
Fuel: Diesel  
Voltage: 230V/400V  
Frequency: 50 Hz  
Manufacturer and type: Baudouin 4M06G35/5  
1500 rpm  
Displacement: 2300 cc.  
Alternator MECC ALTE ECP28-VL4 4 poles  
Noise level at 7 m: 70 dB(A)  
Tank: 100 Lt.  
Length: 2100 mm  
Width: 870 mm  
Height: 1165 mm  
Dry weight: 940 Kg. approx.  
Emission level: not emitted

If you are looking for a product with similar characteristics [CLICK HERE](#).

Non-binding images and technical data.

#### **Product features:**

Phase: Three phase  
Maximum power three phase (KW): 26.4  
Continuous power three phase (KW): 24  
Maximum power three phase (KVA): 33  
Continuous power three phase (KVA): 30  
Fuel: Diesel  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Engine: Baudouin 4M06G35/5  
Emissions Regulations: Not Emitted  
Engine rpm (rpm): 1500  
Speed governor: Electronic  
Starting system: Electric  
Engine capacity (cm<sup>3</sup>): 2300  
Number cylinders: 4  
Alternator: MECC ALTE ECP28-VL/4  
Poles: 4



---

Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 100  
Consumption (L/h): 5.61 at 75% of the load  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 2100  
Width (mm): 870  
Height (mm): 1165  
Dry weight (Kg): 940  
Silenced: Yes  
ATS Switch device : Optional  
Engine manufacturer: Baudouin

