



# PRAMAC GSW110P APERTO CON QUADRO COMANDO AUTOMATICO

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 91.74

Continuous power three phase (KW): 83.07

Maximum power three phase (KVA): 114.67

Continuous power three phase (KVA): 103.84

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: PERKINS 1104C-44TAG2, turbocharged

Emissions Regulations: Stage 2

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 4410

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 8

Cooling: Water

Alternator: Mecc Alte ECP34-2S/4, brushless

Poles: 4

Fuel tank capacity (L): 240

Consumption (L/h): 18 at 75% of the load / 22.6 at 100% of the load

Running time (h): 13.3 at 75% of the load / 10.6 at 100% of the load

Length (mm): 2200

Width (mm): 1000

---

Height (mm): 1743  
Dry weight (Kg): 1170  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Perkins