



# VISA F105GXLVM SILENCED GENSET 100 KVA STAGE V



Product price:

**33.630,00 € tax excluded**

## Product description:

VISA F105GXLVM SILENCED GENSET 100 KVA STAGE V

VISA Genset F105GXLVM is a state-of-the-art three-phase genset designed to provide a reliable and silent power supply, even under the most demanding conditions. With a continuous power output of 80 kW and an FPT-IVECO F36ETVP03 engine that complies with Stage V emissions regulations, this genset is the ideal solution for a wide range of applications, in both industrial and civil applications.

## Key features *VISA Genset F105GXLVM:*

**Powerful and reliable:** The FPT-IVECO F36ETVP03 4-cylinder engine ensures high performance and a long service life.

**Quiet:** Thanks to the Visa silencer model, the noise level is extremely low, ensuring discrete operation.

**Versatile:** The 400 V output voltage and 50 Hz frequency make it compatible with most electrical appliances.

**Economical:** Its low consumption of 20.8 litres/hour at 75% load makes it a cost-effective solution.

**Robust:** The solid construction and high-quality components guarantee a long service life.

**Environmentally friendly:** Compliant with Stage V emissions regulations.

## Why choose the *VISA Genset F105GXLVM?*

**Construction:** Ideal for powering construction equipment and lighting.



Agriculture: Perfect for powering agricultural machinery and irrigation systems.

Events: Suitable for powering sound systems, lighting and other equipment during outdoor events.

Industry: Provides emergency or continuous power for production processes.

**Technical characteristics *VISA Genset F105GXLVM*:**

Phase type: Three-phase

Three-phase continuous power: 100 KVA

Three-phase continuous power: 80 KW

Voltage: 400 V

Frequency: 50 Hz

Motor: FPT-IVECO - F36ETVP03

Engine speed: 1500 rpm

Starting: Electric

Consumption: 20.8 Lt/h at 75% load

Length: 3060 mm

Width: 1200 mm

Height: 2200 mm

Fuel tank: 360 L

Supersilenced

Number of cylinders: 4

Cooling: Water

Electronic Regulator: Standard

Stage V

Silencer Model: Visa

sound pressure: 65dBA(+/-3)@7m

If you are looking for a product such as the VISA then you can browse the entire VISA generator range or other types of products in our catalogue to find the one that best suits your needs.

Images and technical data are not binding.

**Product features:**

Phase: Three phase

Continuous power three phase (KW): 80

Continuous power three phase (KVA): 100

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT-IVECO - F36ETVP03

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3600

Number cylinders: 4

Cooling: Water

Tank capacity (L): 360

Consumption (L/h): at 75% (P.R.P.) 20.8 l/h

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 3060

Width (mm): 1200

Height (mm): 2200

Silenced: Yes

Product type: Generator

Engine manufacturer: FPT Iveco