



Submersible electric pump for LOADED LIQUIDS 6.5KW

Product description:

submersible electric pump for LOADED LIQUIDS 6.5KW

The 6.5 kW submersible electric pump for charged liquids is a robust and reliable solution ideal for pumping wastewater in industrial and civil applications. Featuring a 6.5 kW three-phase motor with a frequency of 50 Hz and a voltage of 400 V, this pump is capable of handling high flow rates even in the presence of soiled liquids with a maximum solids content of 4%. Thanks to its stainless steel construction and IP68 protection, it is particularly suitable for installation in wet and corrosive environments. With a minimum immersion depth of 349 mm and a maximum number of starts per hour of 15, this electric pump guarantees continuous and safe operation and 80 mm delivery diameter allow it to reach high delivery heights, making it ideal for applications in lifting and purification plants.'

Typical applications: 'This electric pump is used in a wide range of applications, including pumping domestic and industrial wastewater, emptying septic tanks, draining construction sites and transferring general cargo liquids.'

Advantages: 'The main advantages of this electric pump are its high reliability, long service life and ability to handle charged liquids with a high solids content.'

Technical characteristics:

Pumped liquid: Waste water

Max. pumped liquid temperature: 40 °C

Maximum density: 1 kg/dm³ Maximum viscosity: 1 mm²/s

Max. solids content: 4 Batteries max. 20 m

Maximum number of starts/hour: 15





Minimum submergence: 349 mm S1 Maximum power consumption: 5.8 KW

Frequency: 50 Hz Voltage: 400 V

Installation weight: 26 Kg Electropump weight 113 Kg Motor model: KC006522H132N3

Nominal power: 6.5 KW Rated current: 11.9 A

Poles: 2

Brand: Caprari

Degree of protection: IP68 Outlet diameter: 80 mm

Type of installation: vertical BAKF-A 2'

Insulation class: H

Pump-side sealing: Mechanical Operation: Continuous (S1)

if you are looking for a product similar to an electric pump click HERE.

Images and data purely indicative.

Product features:

Phase: Three phase Frequency (Hz): 50 Voltage (V): 400

Protection degree: IP68

Pump type: SUBMERSIBLE ELECTRIC PUMP

Motor insulation class: H

Outlet diameter thread type (mm/inches): 80

Nominal current (A): 11.5

Weight (Kg): 113

Nominal Power Kw: 6.5

