

MOSA GE 55FSX Generator Set 55KVA 400V AVR

Product price:

56.442,00 € tax excluded

Product description:

 \mathbb{N}

MOSA GE 495 SSX Generator Set 500KVA 400V

MOSA GE 495 SSX Generator Set 500KVA 400V: Power and reliability for your energy needs

The MOSA GE 495 SSX is a three-phase genset designed to provide a reliable and continuous power supply in various industrial and commercial applications. With a maximum standby power of 500 kVA and a voltage of 400V, this generator can meet the energy needs of a wide range of installations.

Key features:

Powerful and efficient engine: Equipped with a SCANIA DC13 072A 02-13 in-line 6-cylinder engine, the MOSA GE 495 SSX generator offers high performance and low fuel consumption. High capacity: The 580-litre tank provides extended autonomy, reducing the frequency of

High capacity: The 580-litre tank provides extended autonomy, reducing the frequency of refuelling.

Built to last: The robust construction, with watertight base frame and two central lifting hooks, ensures a long service life and easy handling.

Safety and protection: The generator is equipped with numerous safety features, including:

Battery cut-off switch

Low radiator liquid level sensor

Fuel prefilter with water decanter

Oil extraction pump

Ease of use and maintenance: Thanks to the large access doors and intuitive control panel, generator maintenance is quick and easy.

High-quality alternator: The alternator with electronic voltage regulator AVR guarantees a stable and precise voltage, protecting connected devices.

Regulatory compliance: The generator complies with EC directives, ensuring maximum safety and reliability.

R

Technical characteristics:

Ø.

Three-phase Stand-by power: 500 kVA (400 kW) Voltage: 400 V Three-phase power PRP: 450 kVA (360 kW) Three-phase power COP: 350 kVA (280 kW) Frequency: 50 Hz Tank capacity: 580 litres Autonomy (75% PRP): 8.8 h Acoustic power LwA (LpA pressure): 99 dB(A) (74 dB(A) @ 7m) Dry weight: 4445 kg Dimensions (LxWxH): 4100x1520x2150 mm Engine: SCANIA DC13 072A 02-13 Cylinders: 6 in line Displacement: 12700 cm3

If you are looking for a product with similar characteristics CLICK HERE.

Images and data purely indicative.

Product features:

Phase: Three phase Maximum power three phase (KW): 400 Continuous power three phase (KW): 360 Maximum power three phase (KVA): 500 Continuous power three phase (KVA): 450 Frequency (Hz): 50 Engine rpm (rpm): 1500 Speed governor: Electronic Tank capacity (L): 580 Product dimensions (mm): 4100x1520x2150 Running time (h): 8.8 at 75% of the load Acoustic pressure: 99 dB(A) (74 dB(A) @ 7m Voltage regulator: AVR Weight (Kg): 4445 Voltaggio: 400volt