

Generator set 66KVA Silent Stage II



Product price:

12.933,00 € tax excluded

Product description:

Generator set 66KVA Silent Stage II

66KVA Silent Stage II Generator - Power and Reliability

This three-phase generator is the ideal solution for providing emergency or continuous power supply in various industrial and commercial applications. With a maximum power of 66 KVA and a continuous power of 60 KVA, this generator is capable of powering a wide range of electrical equipment, even under high load conditions.

Main features:

Powerful engine: Equipped with a robust FPT N45SM1A diesel engine, synonymous with reliability and durability.

Regulatory compliance: Complies with Stage II emissions regulations, ensuring low environmental impact.

Silence: Thanks to the soundproofing system, the noise level is reduced, allowing use in noise-sensitive environments.

Compact and easy to handle: With small dimensions (2260x1000x1420 mm) and a weight of 1250 kg, it is easy to transport and install.

Autonomy: The 100-liter tank guarantees adequate autonomy for many applications.

Protection: The IP23 protection rating ensures good resistance to dust and water splashes.

Electric start: The electric start makes starting the generator quick and easy.

Technical Features:

Maximum three-phase power: 66 KVA

Continuous three-phase power: 60 KVA

Maximum three-phase power: 53 KW

Continuous three-phase power: 48 KW

Fuel: Diesel
Voltage: 230/400 V
Engine: FPT N45SM1A
Protection rating: IP23
Start: Electric
Tank capacity: 100 lt.
Length: 2260 mm
Width: 1000 mm
Height: 1420 mm
Weight: 1250 Kg

If you are looking for a product with similar characteristics [CLICK HERE](#).

Images and technical data are purely indicative.

Product features:

Phase: Three phase
Maximum power three phase (KW): 53
Continuous power three phase (KW): 48
Maximum power three phase (KVA): 66
Continuous power three phase (KVA): 60
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: FPT N45SM1A
Emissions Regulations: Stage 2
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 4500
Number cylinders: 4
Cylinders' position: In line
Protection degree: IP23
Fuel tank capacity (L): 100
Consumption (L/h): 13.3 at 75% Load
Running time (h): 10.2
Acoustic pressure: 65 dB(A) at 7 m
Length (mm): 2260
Width (mm): 1000
Height (mm): 1420
Dry weight (Kg): 1250
Silenced: Yes

Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR