



ITALTOWER Street-PRO02 Light Tower 4x160W MultiLED

Product price:

3.022,00 € tax excluded

Product description:

ITALTOWER Street-PRO02 4x160W MultiLED Tower Light

ITALTOWER Street-PRO02 4x160W MultiLED Tower Light: Powerful and versatile lighting

ITALTOWER Street-PRO02 is a professional light tower designed to provide intense and uniform lighting in all conditions. Thanks to its 4 x 160W LED projectors, this tower is able to illuminate an area of up to 2400 square metres, providing excellent visibility even in the darkest areas.

Key Features:

Robust construction: Made of galvanised steel, the tower is corrosion and weather resistant, ensuring a long lifespan.

Flexibility: The telescopic galvanised steel pole allows the height of the tower to be adjusted up to 5.5 metres, adapting it to any requirement.

Energy efficiency: Energy-efficient LED floodlights ensure a long service life and reduce running costs.

Transportability: Thanks to its compact closed dimensions (1200x800x2000 mm) and fixed trolley, the tower is easy to transport and position.

Stability: The tower is equipped with a stabilisation system that makes it safe even in high wind conditions up to 80 km/h.

Technical characteristics:

Phase type Single-phase

Frequency (Hz) 50

Type of LED lamps

Telescopic pole Galvanised steel

Illuminated area (m²) 2400

Total lumens (Lm) 87680



Lifting system Manual lifting system
Maximum height (m) 5.5
Dimensions open (mm) 1200 x 1291 x 5500
Dimension closed (mm) 1200 x 800 x 2000
Wind stability (Km/h) 80
Weight (Kg) 260
trolley: Stationary

Are you looking for a product with different characteristics? HERE you can find the entire range of ITALTOWER lighting towers or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the supplier.

Product features:

Phase: Single phase
Type of lamps: LED
Telescopic pole: Galvanized steel
Total lumens (Lm): 87680
Lifting System: Manual lifting system
Open size (mm): 1200 x 1291 x 5500
Closed size (mm): 1200 x 800 x 2000
Stability to wind (Km/h): 80 Km/h
Weight (Kg): 260
Operating temperature range (°C): -30/+50
carello: Stazionaria