



# ITALTOWER Street-PRO02 Light Tower 4x160W MultiLED

**Product price:**

**2.600,00 € tax excluded**

## Product description:

ITALTOWER Street-PRO02 4x160W MultiLED Tower Light

ITALTOWER Street-PRO02 4x160W MultiLED Tower Light: Powerful and versatile lighting

ITALTOWER Street-PRO02 is a professional light tower designed to provide intense and uniform lighting in all conditions. Thanks to its 4 x 160W LED projectors, this tower is able to illuminate an area of up to 2400 square metres, providing excellent visibility even in the darkest areas.

## Key Features:

**Robust construction:** Made of galvanised steel, the tower is corrosion and weather resistant, ensuring a long lifespan.

**Flexibility:** The telescopic galvanised steel pole allows the height of the tower to be adjusted up to 5.5 metres, adapting it to any requirement.

**Energy efficiency:** Energy-efficient LED floodlights ensure a long service life and reduce running costs.

**Transportability:** Thanks to its compact closed dimensions (1200x800x2000 mm) and fixed trolley, the tower is easy to transport and position.

**Stability:** The tower is equipped with a stabilisation system that makes it safe even in high wind conditions up to 80 km/h.

## Technical characteristics:

Phase type Single-phase

Frequency (Hz) 50

Type of LED lamps

Telescopic pole Galvanised steel

Illuminated area (m<sup>2</sup>) 2400

Total lumens (Lm) 87680



Lifting system Manual lifting system  
Maximum height (m) 5.5  
Dimensions open (mm) 1200 x 1291 x 5500  
Dimension closed (mm) 1200 x 800 x 2000  
Wind stability (Km/h) 80  
Weight (Kg) 260  
trolley: Stationary

Are you looking for a product with different characteristics? HERE you can find the entire range of ITALTOWER lighting towers or other specialized brands.

Images and technical data are not binding and may be subject to revisions by the supplier.

**Product features:**

Phase: Single phase  
Type of lamps: LED  
Telescopic pole: Galvanized steel  
Total lumens (Lm): 87680  
Lifting System: Manual lifting system  
Open size (mm): 1200 x 1291 x 5500  
Closed size (mm): 1200 x 800 x 2000  
Stability to wind (Km/h): 80 Km/h  
Weight (Kg): 260  
Operating temperature range (°C): -30/+50  
carello: Stazionaria