



PRAMAC GBW22P GENERATOR 22KVA THREE-PHASE STAGEV MANUAL CONTROL PANEL SUPERSILENCED

Product price:

10.984,00 € tax excluded

Product description:

PRAMAC GBW22P GENERATOR 22KVA THREE-PHASE SUPERSILENCED MANUAL STAGE V

The PRAMAC GBW22P is a powerful 22 kVA three-phase generator designed to provide a reliable emergency or back-up power supply in a variety of applications. Thanks to the Perkins 404J-22G engine and the Mecc Alte ECP28-M4 C alternator, this generator offers high performance and a long service life.

Key features:

Power: With a maximum output of 22 kVA, this generator can power a wide range of electrical devices, from small tools to larger equipment.

Quiet: Thanks to the soundproofing system, the noise level is extremely low, making it ideal for applications requiring low noise impact.

Compact and manoeuvrable: The small size and relatively light weight make the generator easy to transport and handle.

Reliable engine: The Perkins engine is known for its robustness and reliability, ensuring long lasting operation.

Regulatory compliance: The generator complies with Stage V emissions regulations, ensuring a low environmental impact.

Manual control panel: The manual control panel makes it easy to manage all generator functions.

Versatile configuration: Thanks to several sockets, the generator can be connected to a wide range of electrical devices.

Technical specifications PRAMAC GBW22P:

Phase type Three-phase

Maximum three-phase power (KW) 17.60

Three-phase continuous power (KW) 16.10

Maximum three-phase power (KVA) 22

Three-phase continuous use power (KVA) 20.12

Fuel Diesel

Frequency (Hz) 50

Voltage (V) 400

Socket configuration

- 400V 32A 3P+N+E CEE n 1

- 400V 16A 3P+N+E CEE n 1

- 230V 16A 2P+E CEE n 2

- 230V 16A SCHUKO n 1

Perkins 404J-22G motor

RPM regulator Mechanical

Electric Starter

Displacement (cm³) 2220

Number of cylinders

Cylinder arrangement In-line

Oil capacity (L) 6

Cooling Water

Alternator Mecc Alte ECP28-M4 C

Number of poles 4

Fuel tank capacity (L) 51

Consumption (L/h) 4 at 75% load

Autonomy (h) 12.75 at 75% load

Acoustic power 95 dB(A)

Acoustic pressure 66 dB(A) at 7 m

Length (mm) 1645

Width (mm) 870

Height (mm) 1060

Dry weight (kg) 546

Silenced Yes

Super silenced Yes

Product type Generator set

Switchgear ATS Optional

AVR voltage regulator

Stage 5 emissions standard

Looking for a generator with different technical specifications? Check out the dedicated section for PRAMAC generators or other specialized brands.

Images and technical data are not binding.

Product features:

Phase: Three phase

Maximum power three phase (KW):

Continuous power three phase (KW):

Maximum power three phase (KVA):

Continuous power three phase (KVA):

Fuel: Diesel

Voltage (V): 400

Sockets configuration:

Engine: Perkins 404J-22G

Emissions Regulations: Stage 5

Speed governor: Mechanical

Starting system:

Engine capacity (cm³):

Cylinders' position: In line

Oil capacity (L): 6

Cooling: Water

Alternator:

Poles: 4

Fuel tank capacity (L): 51

Consumption (L/h):

Running time (h):

Acoustic power: 95 dB(A)

Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 1645

Width (mm): 870

Height (mm): 1072

Dry weight (Kg):

Silenced: Yes

Super silenced: Yes

Product type: Generator

ATS Switch device : Optional

Engine manufacturer: Perkins