



MOSA MPA50H Motopump for dark water 500L/min

Product price:

701,00 € tax excluded

Product description:

MOSA MPA50H Mud Water Pump 500L/min

The MOSA MPA50H is a high-quality motor pump designed for draining dirty water.

Thanks to its robust structure and powerful Honda GX200 engine.

The MOSA MPA50H is the ideal choice for those looking for a powerful, reliable, and versatile mud water pump.

Thanks to its advanced technical features, it can meet the needs of individuals, professionals, and farms.

Main Features MOSA MPA50H:

Powerful Engine: The Honda GX200 4-stroke petrol engine ensures high performance and reliability.

High Flow Rate: The MOSA MPA50H offers a maximum flow rate of 500 liters per minute, allowing you to quickly complete even the most demanding tasks.

High Head: The pump can lift water up to 90 meters high, making it suitable for various applications.

Effective Suction: The maximum suction lift of 8 meters allows you to draw water even from deep wells or tanks.

Versatile: The MOSA MPA50H can be used for various applications, including:

Draining dirty water from construction sites, ditches, ponds, and swimming pools.





Irrigation of fields and gardens, and much more!

Technical Specifications *MOSA MPA50H:*

Suction connection diameter: 50 mm (2 inches) Connection thread: BSP pipe external thread

Delivery volume: 500 L/min Maximum suction lift: 8 m

Engine: Honda GX200 high speed

Engine type: 4-stroke air-cooled forced air gasoline engine

Displacement: 196 cm³

Continuous rated power: 3.7 kW Maximum rated power: 4.6 kW Engine speed: 3,600 rpm Fuel tank capacity: 3.1 liters

Operating time: Approximately 1.5 hours

Starting: Recoil

Viscosity: Clear water Net weight: 34.6 kg

Dimensions: 550 x 437 x 457 mm

Fuel: Gasoline Total head: 90 m

Discharge connection diameter: 50 mm (2 inches) / 25 mm (1 inch) x 2

If you are looking for a product with similar features CLICK HERE.

Images and technical data are purely indicative.

Product features:

Fuel: Gasoline

Engine: HONDA GX200 high rotation

Engine rpm (rpm): 3.600 Starting system: Pull starter Engine capacity (cm³): 196

Nominal power continuous: 3.7 kW

Product dimensions (mm): 550 x 437 x 457

Total head (m): 90

Fuel tank capacity (L): 3.1

Net weight kg: 34,6

connection diameter: Suction: 50 mm (2 in) Connection thread: BSP external pipe thread

delivery volume: 500 L/min Maximum suction head: 8 m





Motor type: Air-cooled 4-stroke petrol engine

Max Rated Power: 4.6 kW

tempo di funzionamento: approx. 1.5 hours

Viscosity: Clear water

Connection diameter - Drain: 50 mm (2 in) / 25 mm (1 in)×2

