



## MOSA EPI50-750 Electric submersible pumps 330L/min

**Product price:**

**524,00 € tax excluded**

### **Product description:**

MOSA EPI50-750 Submersible Electric Pumps 330L/min

MOSA EPI50-750 Submersible Electric Pumps 330L/min: Power and Reliability for Your Pumping Needs

The MOSA EPI50-750 is a high-performance submersible electric pump designed to offer efficiency and reliability in various pumping applications. With a maximum flow rate of 330 liters per minute and a total head of 15 meters, this pump is ideal for draining clear and slightly dirty water, even in situations requiring greater lifting power.

Main Features MOSA EPI50-750 Submersible Electric Pumps 330L/min:

**High Flow Rate:** With a flow rate of 330 L/min, the EPI50-750 is able to quickly move large volumes of water, reducing working times.

**PBX Polyurethane Impeller:** The PBX polyurethane impeller ensures wear resistance and durability over time, even in the presence of abrasive liquids.

**Compact and Lightweight Design:** With a weight of only 15 kg and dimensions of 245 x 245 x 450 mm, this pump is easy to transport and install in confined spaces.

**Energy Efficiency:** Current (A): 6 A - 10 A, the EPI50-750 offers an excellent ratio between performance and energy consumption.

**Higher Head:** With a head of 15 meters, this pump is able to lift water to a greater height than other models, making it suitable for various applications.



Reliability: Built with high-quality materials and designed for continuous operation, this electric pump ensures consistent performance over time.

**Technical Features** MOSA EPI50-750 Submersible Electric Pumps 330L/min:

Connection diameter: 50 mm (2")

Total head (m): 15

Impeller: PBX Polyurethane

Pump type: Electric

Current (A): 6 A - 10 A

Net weight kg: 15 Kg

Product dimensions (mm): 245 x 245 x 450

Delivery volume: 330 L/min

If you are looking for a product with similar features [CLICK HERE](#).

Images and technical data are purely indicative.

**Product features:**

Pump type: Electric

Product dimensions (mm): 245 x 245 x 450

Total head (m): 15

Current (A): 6 A - 10 A

Girante: PBX Polyurethane

Net weight kg: 15.5 Kg

delivery volume: 330

Connection diameter: 50 mm (2")