

GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV

Product price:

10.708,00 € tax excluded

Product description:

 $\langle n \rangle$

GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV

GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV is an advanced mobile lighting solution,

designed to offer high performance and reliability in various applications, from construction sites to outdoor events.

Key Features:

RI)

Powerful and Efficient Lighting:

Equipped with 4 x 320W LED projectors (G5 model), it guarantees a luminous flux of 211,200 Lm and an illuminated area of 9,200 m² (1 lux min).

LEDs offer a long lifespan, with over 50,000 hours of operation.

Robust and Accessible Design:

Compact dimensions to facilitate transport and storage (minimum dimensions: 2156 x 1400 x 2403 mm, maximum: 3096 x 2166 x 8334 mm).

"Gull-wing" doors for easy access to internal components.

PrestaShop



Simplified control panel with DSE L401-MKII digital controller.

Efficiency and Sustainability:

Kubota Z482 2-cylinder, liquid-cooled engine, to reduce fuel consumption and CO2 emissions.

Large fuel tank (200/180 liters) for 257 hours of autonomy.

Liquid containment (110%) to prevent leaks.

Mobility and Robustness:

Road trailer with folding drawbar for easy transport.

Wind resistance up to 110 km/h.

Hydraulic mast lifting system and 340° rotation.

Dry weight of 923 kg.

Additional Features:

Output socket (16A) and input plug (16A).

Standard timer and optional darkness sensor.

Average sound pressure of 60 dB(A) @ 7m.

Alternator (50/60 Hz): 3.5kVA 230V / 4.2kV 240V.

Technical Specifications GENERAC GLT4-A K2 LIGHT TOWER 4x320W LED STAGEV:

Minimum dimensions (Length x Width x Height): 2156 x 1400 x 2403 mm Maximum dimensions (Length x Width x Height): 3096 x 2166 x 8334 mm Dry weight: 923 kg Mast lifting system: Hydraulic

Are you looking for a lighting tower with different technical characteristics? HERE you can find the entire range of GENERAC lighting towers or other specialized brands.

PrestaShop

Non-binding images and technical data.

Product features:

Ø.

Engine: Kubota Z482 Emissions Regulations: STAGE V Engine rpm (rpm): 1500/1800 Number cylinders: 2 Cooling: Liquid Alternator: 3,5kVA 230V / 4,2kV 240V Tank capacity (L): (gross/net) 200/180I Type of lamps: LED Illuminated area (m²): 9200 Total lumens (Lm): 211200 Lm Mast rotation: 340° Stability to wind (Km/h): 110km/h Running time (h): 257 h Acoustic pressure: 60 dB(A) @ 7m Dry weight (Kg): 923 Type of lifting: Idraulico Output socket: 1 (16A) Dimensioni max. (mm): 3096 x 2166 x 8334 minimum dimensions mm: 2156 x 1400 x 2403 Liquid containment: (110%): yes Output socket : 1 (16A)