



# LUXTOWER LUXB1 Light Tower LED IP69K 4x100W

Product price:

**5.841,00 € tax excluded**

## Product description:

LUXTOWER LUXB1 LED LIGHT TOWER IP69K 4x100W

The LUXTOWER LUXB1 LED Light Tower IP69K 4x100W is the ideal solution for those who need a mobile, efficient, and completely autonomous lighting system.

Thanks to its 100% battery-powered operation, it guarantees zero emissions, no fuel consumption, and no maintenance, making it perfect for construction sites, events, and noise-sensitive environments.

Equipped with 4 x 100W LED floodlights with IP69K protection, the LUXTOWER LUXB1 Light Tower offers powerful, uniform lighting that is resistant to the elements, covering an area of up to 2650 m<sup>2</sup>. The telescopic pole reaches a maximum height of 5.5 meters and ensures wind stability up to 110 km/h.

## Technical Features LUXTOWER LUXB1 Light Tower:

Power supply: 100% battery-powered (2 AGM 12V - 140Ah batteries)

Floodlights: 4 x 100W LED (IP69K)

Illuminated area: up to 2650 m<sup>2</sup>

Telescopic pole height: 5.5 m (vertical)

Wind stability: up to 110 km/h

Operating time: 11 hours





Charging time: 9 hours

Lifting system: manual

Total weight: 352 kg

Minimum dimensions: 1190 x 800 x 2400 mm

Maximum dimensions: 1500 x 900 x 5500 mm

Built-in charger: 230V - 50Hz

Input socket: 16V - 50Hz

### 100% Battery and Maximum Autonomy LUXTOWER LUXB1

One of the strengths of the LUXTOWER LUXB1 4x100W is its full battery system, allowing it to operate without the need for external power.

Equipped with 2 AGM batteries (12V - 140Ah) and an integrated charger, this light tower ensures 11 hours of operation with a charging time of only 9 hours.

### Robust Structure and Advanced Features LUXTOWER LUXB1

Made with a galvanized and powder-coated metal body, the LUXTOWER LED IP69K 4x100W is designed to withstand extreme conditions.

The advanced control panel includes a battery status indicator, timer, work mode selector, and external power indicator, providing full control over operations.

### Benefits of the LUXTOWER LUXB1 LED IP69K 4x100W

100% battery-powered – Zero emissions and fuel costs

11-hour autonomy with only 9 hours of charging

4x100W IP69K LED floodlights for high resistance and performance

Lighting coverage up to 2650 m<sup>2</sup> for maximum visibility

Telescopic pole up to 5.5 meters with wind stability of 110 km/h

Silent operation – No noise emissions





---

No maintenance required – An eco-friendly and efficient solution

Perfect for construction sites, events, emergencies, and industrial applications, the LUXTOWER LUXB1 LED IP69K 4x100W is the ideal choice for professional, reliable, and sustainable lighting.

Looking for other light towers like the LUXTOWER LUXB1 LED IP69K? [HERE](#) you can explore our catalog dedicated to LUXTOWER light towers or other brands.

Images and technical data are non-binding. Please always consult the technical datasheet provided by the manufacturer. Manel Service assumes no responsibility for any changes made by the manufacturer.

#### **Product features:**

Phase: Single phase

Maximum height (m): 5.5

Type of lamps: LED (IP69K)

Lamps: 4 x 100 W

Telescopic pole: Vertical

Illuminated area (m<sup>2</sup>): 2650

Lifting System: Manual lifting system

Stability to wind (Km/h): 110

Running time (h): 11

Product type: Light tower

Weight (Kg): 352

Charging time [h]: 9

Battery type: AMG

Battery cycle: 500

Dimensioni min. (mm): 1190 X 800 X 2400

Dimensioni max. (mm): 1500 X 900 X 5500

Number of units: 2

Single unit power (V/Ah): 12 - 140

Battery charger (V/Hz): 230 - 50

Input socket (V/Hz): 16 - 50

