

# GENERATOR SET 44KVA SILENT STAGEV



Product price:

**14.703,00 € tax excluded**

## Product description:

44KVA Silenced Generator Set STAGEV

44KVA Silenced Generator Set STAGEV is a high-quality three-phase generator, designed to provide reliable and quiet power in a wide range of applications. With a maximum power of 44 kVA (40 kW), this generator set is ideal for powering construction sites, outdoor events, emergency situations and other applications that require a stable and quiet power source.

## Key Features:

### YANMAR Stage V Engine:

The YANMAR 4TNV98C engine ensures high efficiency and low emissions, in compliance with Stage V regulations.

The engine speed of 1500 rpm ensures stable and constant power delivery.

### LINZ Alternator:

The LINZ PRO18 ME/4 alternator provides a stable voltage of 230/400V at 50Hz, ensuring compatibility with various equipment.

### Superior Quietness:

Thanks to its super silenced configuration, this generator set produces only 62 dB(A) at 7 meters, making it ideal for noise-sensitive environments.

### Autonomy and Capacity:



The 120-liter fuel tank offers excellent autonomy, with a consumption of 7.2 lt/h at 75% load.

#### Robust and Reliable Design:

With a dry weight of 1280 Kg and dimensions of 2260x900x1420 mm, this generator set is built to last.

Water cooling ensures efficient operation even under high load conditions.

#### Advanced Functionality:

Electronic speed governor for optimal stability.

Electric start for easy and quick start-up.

#### Technical Specifications:

**Phase type:** Single phase/Three phase

**Maximum three-phase power:** 40 kW

**Maximum three-phase power:** 44 kVA

**Frequency:** 50 Hz

**Voltage:** 230 / 400 V

**Engine:** YANMAR 4TNV98C

**Engine speed:** 1500 rpm

**Speed governor:** Electronic

**Start:** Electric

**Displacement:** 3319 cm<sup>3</sup>

**Number of cylinders:** 4

**Cooling:** Water

**Alternator:** LINZ PRO18 ME/4

**Number of poles:** 4

**Fuel tank capacity:** 120 liters

**Consumption:** 7.2 lt/h (specific consumption at 75% load)

**Sound pressure:** 62 dB(A) at 7 meters

**Length:** 2260 mm

**Width:** 900 mm

**Height:** 1420 mm

**Dry weight:** 1280 Kg

**Silenced:** Yes

**Super silenced:** Yes

**Product type:** Generator set

**Engine brand:** LINZ

**Emission standard:** Stage 5





If you are looking for a product with similar characteristics click [HERE](#).

Images and technical data are not binding. Always consult the technical data sheet issued by the manufacturer.

Manel Service does not assume responsibility for any changes made by the manufacturer.

### Product features:

Phase: Single phase / Three phase

Maximum power three phase (KW): 40

Maximum power three phase (KVA): 44

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: YANMAR 4TNV98CT

Emissions Regulations: Stage 5

Engine rpm (rpm): 1500

Speed governor: Electronic

Starting system: Elettrico

Engine capacity (cm<sup>3</sup>): 3319

Number cylinders: 4

Cooling: Water

Alternator: LINZ PRO18 ME/4

Poles: 4

Fuel tank capacity (L): 120

Consumption (L/h): 7.2 lt/h Specific consumption at 75% load

Acoustic pressure: 62 dB(A) at 7 m

Length (mm): 2260

Width (mm): 900

Height (mm): 1420

Dry weight (Kg): 1280

Silenced: Yes

Super silenced: Yes

Product type: Generator

Engine manufacturer: LINZ

