



# UNIMEC MINITRANSPORTER FG33A EXPANDABLE 800KG

**Product price:**

**9.086,00 € tax excluded**

## **Product description:**

UNIMEC FG33A EXPANDABLE MINITRANSPORTER 800KG

UNIMEC EXPANDABLE MINITRANSPORTER 800KG is a versatile and powerful tracked mini-transporter, designed to handle a wide range of applications in challenging environments and confined spaces.

With a load capacity of 800 kg, this mini-transporter offers an exceptional combination of power, maneuverability, and robustness.

Key Features of UNIMEC EXPANDABLE MINITRANSPORTER 800KG:

### **Powerful Engine:**

Available with a Honda GX270 gasoline engine (Hp 9) or a Yanmar L100 diesel engine (Hp 10), to suit different power needs.

The pull start ensures easy and quick start-up.

### **Advanced Hydraulic System:**

Equipped with an EPRM.L315 hydraulic motor and PLP 10-4 3/4 UNIT hydraulic pumps, with a displacement of 3/4 unit x 4cc/rev.

The oil pressure of 130 bar ensures high thrust and precise control.



---

### Exceptional Performance:

Reaches a maximum speed of 2.3/3.2 km/h, allowing for rapid and efficient movement.

The permissible slope of 46% (25°) allows for easy overcoming of obstacles and rough terrain.

### Robust and Compact Design:

With dimensions of 1770x1060x1150 mm and a dry weight of 480 kg, this mini-transporter is easy to transport and maneuver.

The minimum ground clearance of 120 mm and the 180x72x37 mm tracks ensure excellent stability on any terrain.

### High Load Capacity:

The 800 kg payload allows for safe and efficient transport of heavy loads.

The 800 kg flat ground load capacity ensures optimal stability during transport.

### Technical Specifications:

Fuel: Gasoline

Engine: Honda GX270 (Hp 9)

Length: 1770 mm

Width: 1060 mm

Height: 1150 mm

Dry weight: 480 Kg

Flat ground load capacity: 800 Kg

Payload: 800 Kg

Engine: Yanmar L100 (Hp 10)

Hydraulic motor: EPRM.L315

Minimum ground clearance: 120 mm

Track size: 180x72x37 mm





Maximum speed: 2.3/3.2 km/h

Hydraulic pumps: PLP 10-4 3/4 UNIT

Pump displacement: 3/4 unit x 4cc/rev

Oil pressure: 130 bar

Permissible slope: 46% (25°)

Included:

- AGRICULTURAL DUMP BOX
- HP 9.00 PULL START/
- EXPANDABLE TRACKS/
- OPERATOR PLATFORM

Looking for a tracked trolley with different technical characteristics? [HERE](#) you can find the full range of UNIMEC tracked trolleys or other specialized brands.

Images and technical data are not binding. Always consult the technical data sheet issued by the manufacturer.

Manel Service does not assume responsibility for any changes made by the manufacturer.

### **Product features:**

Fuel: Gasoline

Engine: Tear Off - Honda GX270 (Hp 9)

Length (mm): 1770

Width (mm): 1060

Height (mm): 1150

Dry weight (Kg): 480

Load capacity (Kg): 800

Capacità di carico in piano (Kg): 800

hydraulic motor: EPRM.L315

Min. ground clearance (mm): 120

Track size (mm): 180x72x37

Maximum speed (km/h): 2,3/3,2

Hydraulic pumps: PLP 10-4 3/4 UNITA



---

Pump displacement: 3/4 unita x 4cc/giro  
Oil pressure: 130 bar  
Permitted gradient % (incl.): 46% (25°)