



# PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 176

Continuous power three phase (KW): 162.14

Maximum power three phase (KVA): 220

Continuous power three phase (KVA): 202.67

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: VOLVO TAD733GE, turbo intercooled

Emissions Regulations: Stage 2

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 7150

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 34

Cooling: Water

Alternator: Mecc Alte ECO38-2SN/4, brushless

Poles: 4

Fuel tank capacity (L): 400

Consumption (L/h): 34.9 at 75% of the load / 46.5 at 100% of the load

Running time (h): 11.5 at 75% of the load / 8.6 at 100% of the load

Length (mm): 2650

Width (mm): 1180

---

Height (mm): 1965  
Dry weight (Kg): 2026  
Silenced: No  
Super silenced: No  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Volvo