



## PRAMAC GSW50Y COFANATO CON QUADRO COMANDO AUTOMATICO

## **Product description:**

## **Product features:**

Phase: Three phase

Maximum power three phase (KW): 37.03 Continuous power three phase (KW): 35.18 Maximum power three phase (KVA): 46.29 Continuous power three phase (KVA): 43.97

Fuel: Diesel

Frequency (Hz): 50 Voltage (V): 400

Sockets configuration: 1 x 400V 63A 3P+N+T Engine: Yanmar 4TNV98T-ZGPGE, turbocharged

**Emissions Regulations: Stage 3A** 

Speed governor: Electronic Starting system: Electric Engine capacity (cm³): 3319

Number cylinders: 4 Cylinders' position: In line Oil capacity (L): 11.2

Cooling: Water

Alternator: Mecc Alte ECO/P32-3S/4, brushless

Poles: 4

Fuel tank capacity (L): 68

Consumption (L/h): 8.3 at 75% of the load / 11.1 at 100% of the load Running time (h): 8.2 at 75% of the load / 6.1 at 100% of the load

Acoustic power: 95 dB(A)





Acoustic pressure: 66 dB(A) at 7 m

Length (mm): 2000 Width (mm): 920 Height (mm): 1310 Dry weight (Kg): 839

Silenced: Yes

Super silenced: Yes Product type: Generator ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: Yanmar

