



# PRAMAC GSW10Y COFANATO CON QUADRO COMANDO MANUALE (MCP)

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 53.14

Continuous power three phase (KW): 48.18

Maximum power three phase (KVA): 66.43

Continuous power three phase (KVA): 60.22

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT NEF45SM1A, turbo intercooled

Emissions Regulations: Stage 2

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 4500

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 12.8

Cooling: Water

Alternator: Mecc Alte ECO/P32-2L/4, brushless

Poles: 4

Fuel tank capacity (L): 240

Consumption (L/h): 10.2 at 75% of the load / 13.7 at 100% of the load

Running time (h): 23.4 at 75% of the load / 17.5 at 100% of the load

Length (mm): 2200

Width (mm): 1000

Height (mm): 1743

Dry weight (Kg): 1123

Silenced: No

Super silenced: No

ATS Switch device : Optional

Voltage regulator: AVR

Engine manufacturer: FPT Iveco