



PRAMAC GSW80I COFANATO CON QUADRO COMANDO MANUALE

Product description:

Product features:

Phase: Three phase

Maximum power three phase (KW): 65.94

Continuous power three phase (KW): 59.95

Maximum power three phase (KVA): 82.42

Continuous power three phase (KVA): 74.94

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: FPT NEF45SM2A, turbocharged

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 4500

Number cylinders: 4

Cylinders' position: In line

Oil capacity (L): 12.8

Cooling: Water

Alternator: Mecc Alte ECO/P32-3L/4, brushless

Poles: 4

Fuel tank capacity (L): 209

Consumption (L/h): 12.8 at 75% of the load / 17.2 at 100% of the load

Running time (h): 16.3 at 75% of the load / 12.2 at 100% of the load

Acoustic power: 94 dB(A)

Acoustic pressure: 65 dB(A) at 7 m

Length (mm): 2400

Width (mm): 1000
Height (mm): 1530
Dry weight (Kg): 1426
Silenced: Yes
Super silenced: Yes
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: FPT Iveco