

# PRAMAC W 220 TDC



## Product description:

PRAMAC W220 TDC MOTORWELDER 5.5KW

PRAMAC W220 TDC is a motorwelder, light and compact, equipped with a Honda GX390 Recoil gasoline engine capable of delivering a power of 5.5KW.

PRAMAC power welders are your reliable choice, when you are looking for a machine for small repairs, or for more demanding craft applications.

With a 220 A output you can use rutile, basic or cellulosic electrodes up to 5 mm in diameter.

Mechanical adjustment of the welding current.

Reliability, sturdiness and silence to meet all requirements.

## TECHNICAL FEATURES PRAMAC W220 TDC

Maximum single-phase output: 2.4 KW

Continuous use single-phase output: 2 KW

Maximum three-phase power: 5.5 KW

Continuous use three-phase power: 4.16 KW

Fuel: Gasoline

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: Honda GX390 Recoil

Start: Tear-off

Welding Current: 40-220 A

Min/max Welding Voltage: 21.6 V / 28.8 V

Electrode diameter: 5 mm

Consumption: 2.2 at 75% load

Length: 875 mm

Width: 620 mm  
Height: 600 mm  
Weight: 80 Kg

For more information about this and similar products do not hesitate to contact us.  
Images and technical data not binding.

**Product features:**

Phase: Single phase / Three phase  
Maximum power single phase (KW): 2.4  
Continuous power single phase (KW): 2  
Maximum power single phase (KVA): 2.7  
Continuous power single phase (KVA): 2.3  
Maximum power three phase (KW): 5.5  
Continuous power three phase (KW): 4.16  
Maximum power three phase (KVA): 6.1  
Continuous power three phase (KVA): 5.2  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230 / 400  
Sockets configuration: 1 x 400V 16A 3P+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO  
Engine: Honda GX390 Recoil, naturally aspirated  
Speed governor: Mechanical  
Starting system: Pull starter  
Engine capacity (cm<sup>3</sup>): 389  
Oil capacity (L): 1.1  
Cooling: Air  
Welding current (A): 40-220  
Welding voltage min/max (V): 21.6 / 28.8  
Diameter electrodes (mm): 5  
Fuel tank capacity (L): 6.1  
Consumption (L/h): 2.2 at 75% of the load  
Running time (h): 2.8 at 75% of the load  
Acoustic power: 97 dB(A)  
Acoustic pressure: 72 dB(A) at 7 m  
Length (mm): 875  
Width (mm): 620  
Height (mm): 600  
Dry weight (Kg): 80  
Silenced: No  
Super silenced: No

---

ATS Switch device : No  
Voltage regulator: No  
Engine manufacturer: Honda