

PRAMAC W 220 TDC



Product description:

PRAMAC W220 TDC MOTORWELDER 5.5KW

PRAMAC W220 TDC is a motorwelder, light and compact, equipped with a Honda GX390 Recoil gasoline engine capable of delivering a power of 5.5KW.

PRAMAC power welders are your reliable choice, when you are looking for a machine for small repairs, or for more demanding craft applications.

With a 220 A output you can use rutile, basic or cellulosic electrodes up to 5 mm in diameter.

Mechanical adjustment of the welding current.

Reliability, sturdiness and silence to meet all requirements.

TECHNICAL FEATURES PRAMAC W220 TDC

Maximum single-phase output: 2.4 KW

Continuous use single-phase output: 2 KW

Maximum three-phase power: 5.5 KW

Continuous use three-phase power: 4.16 KW

Fuel: Gasoline

Voltage: 230 V / 400 V

Frequency: 50 Hz

Motor: Honda GX390 Recoil

Start: Tear-off

Welding Current: 40-220 A

Min/max Welding Voltage: 21.6 V / 28.8 V

Electrode diameter: 5 mm

Consumption: 2.2 at 75% load

Length: 875 mm

Width: 620 mm
Height: 600 mm
Weight: 80 Kg

For more information about this and similar products do not hesitate to contact us.
Images and technical data not binding.

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 2.4

Continuous power single phase (KW): 2

Maximum power single phase (KVA): 2.7

Continuous power single phase (KVA): 2.3

Maximum power three phase (KW): 5.5

Continuous power three phase (KW): 4.16

Maximum power three phase (KVA): 6.1

Continuous power three phase (KVA): 5.2

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+T CEE - 1 x 230V 16A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Honda GX390 Recoil, naturally aspirated

Speed governor: Mechanical

Starting system: Pull starter

Engine capacity (cm³): 389

Oil capacity (L): 1.1

Cooling: Air

Welding current (A): 40-220

Welding voltage min/max (V): 21.6 / 28.8

Diameter electrodes (mm): 5

Fuel tank capacity (L): 6.1

Consumption (L/h): 2.2 at 75% of the load

Running time (h): 2.8 at 75% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 72 dB(A) at 7 m

Length (mm): 875

Width (mm): 620

Height (mm): 600

Dry weight (Kg): 80

Silenced: No

Super silenced: No

ATS Switch device : No

Voltage regulator: No

Engine manufacturer: Honda