



# PRAMAC GSW145V COFANATO CON QUADRO COMANDO AUTOMATICO

## Product description:

## Product features:

Phase: Three phase

Maximum power three phase (KW): 117.98

Continuous power three phase (KW): 105.9

Maximum power three phase (KVA): 147.48

Continuous power three phase (KVA): 132.38

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 400

Engine: VOLVO TAD750GE, turbo intercooled

Emissions Regulations: Stage 3A

Speed governor: Electronic

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 7150

Number cylinders: 6

Cylinders' position: In line

Oil capacity (L): 20

Cooling: Water

Alternator: Mecc Alte ECP34-1L, brushless

Poles: 4

Fuel tank capacity (L): 350

Consumption (L/h): 25.5 at 75% of the load / 31 at 100% of the load

Running time (h): 13.7 at 75% of the load / 11.3 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 68 dB(A) at 7 m





Length (mm): 3400  
Width (mm): 1250  
Height (mm): 1770  
Dry weight (Kg): 2204  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Volvo