



PRAMAC SP12000 THREE PHASE

Product price:

6.367,50 € tax excluded

Product description:

Motore Honda Serie GX. Raffreddamento ad aria. Batteria fornita di serie. Protezione Oil Guard. Tubazioni telaio maggiorate. Serbatoio maggiorato. Bandelle laterali di protezione

L'immagine è puramente indicativa

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 6

Continuous power single phase (KW): 5.44

Maximum power single phase (KVA): 7.5

Continuous power single phase (KVA): 6.8

Maximum power three phase (KW): 11.1

Continuous power three phase (KW): 9.4

Maximum power three phase (KVA): 13.8

Continuous power three phase (KVA): 11.8

Fuel: Gasoline

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 400V 32A 3P+N+T CEE - 3 x 230V 16A SCHUKO

Engine: Honda GX630, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric



Engine capacity (cm³): 688
Oil capacity (L): 1.9
Cooling: Air
Alternator: Brushless
Poles: 2
Fuel tank capacity (L): 24
Consumption (L/h): 4.23 at 75% of the load / 5.63 at 100% of the load
Running time (h): 5.67 at 75% of the load / 4.26 at 100% of the load
Acoustic power: 96 dB(A)
Acoustic pressure: 72 dB(A) at 7 m
Length (mm): 960
Width (mm): 641
Height (mm): 667
Dry weight (Kg): 170
Silenced: No
Super silenced: No
Product type: Generator
ATS Switch device : No
Voltage regulator: AVR
Engine manufacturer: Honda