



PRAMAC P11000 SINGLE PHASE AMF



Product price:

7.635,00 € tax excluded

Product description:

PRAMAC P11000 Single-phase 9.7 KW Super Silent Generator

The PRAMAC P11000 single-phase generator has a power output of 9.7 KW, powered by a diesel engine running at 3000 RPM. The PRAMAC P11000 generator is equipped with electric start. The alternator of the PRAMAC P11000 generator features a capacitor voltage regulator. The Yanmar diesel engine makes the P11000 generator very reliable as it is built and designed using high-quality materials.

Thanks to its casing, it can be considered super silent, and with its compact dimensions, it can be easily handled and transported. The PRAMAC P11000 single-phase generator is suitable for outdoor use in small construction sites or for small outdoor jobs.

Technical features of the PRAMAC P11000 AMF Single-phase generator:

- Maximum Single-phase Power: 9.7 KW
- Continuous Single-phase Power: 9 KW
- Fuel: Diesel
- Voltage: 230 V
- Frequency: 50 Hz
- Engine: Yanmar 3TNV70-HGE
- Starting System: Electric
- Consumption: 3.97 Lt/h at 100% load
- Length: 1400 mm
- Width: 650 mm
- Height: 975 mm
- Weight: 325 Kg





CONTROL PANEL

Controls:

- Start Key: OFF - ON - START

Instrumentation:

- Voltmeter

- Hour Counter

- Low Oil Pressure Indicator

Protections:

- Circuit Breaker

- Automatic with AMF switch

Outlets:

- N.2 2P+T CEE 230V 16A IP44

- N.1 2P+T CEE 230V 32A IP44

The PRAMAC P11000 power generator is a professional diesel generator developed by Pramac with a diesel engine in a soundproofed and enclosed version, ideal for use in residential areas. The PRAMAC P11000 power generator, with its quiet operation, is the ideal generator for use in residential areas or outside working hours.

The P11000 generator is equipped with top-quality components and complete instrumentation for site use or to cope with any power outages.

If you are looking for a generator like the P11000 AMF single-phase power generator, we recommend browsing our catalog of land-based generators to find the one that best suits your needs.

Images and technical data are non-binding.



Product features:

Phase: Single phase

Maximum power single phase (KW): 9.7

Continuous power single phase (KW): 9

Maximum power single phase (KVA): 10.8

Continuous power single phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 2 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE

Engine: Yanmar 3TNV70-HGE, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 854

Oil capacity (L): 3.8

Cooling: Water

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 3.04 at 75% of the load / 3.96 at 100% of the load

Running time (h): 7.87 at 75% of the load / 6.05 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 1400

Width (mm): 650

Height (mm): 975

Dry weight (Kg): 325

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Yes

Voltage regulator: Capacitor

Engine manufacturer: Yanmar