

PRAMAC P11000 THREE PHASE AMF



Product description:

PRAMAC P11000 Single/Three Phase 8.6 KW Super Silent AMF Generator

The PRAMAC P11000 single/three phase generator with an 8.6 KW diesel engine at 3000 rpm. The PRAMAC P11000 generator is equipped with electric start. The alternator of the PRAMAC P11000 generator has a compound voltage regulator. The Yanmar diesel engine makes the P11000 generator highly reliable as it is built and designed using top-quality materials. Its casing makes it super silent and, with its compact size, it can be easily handled and transported. The PRAMAC P11000 single/three phase generator is suitable for outdoor use in small construction sites or for small outdoor jobs.

Technical Specifications of the PRAMAC P11000 AMF Single/Three Phase Generator:

Max Single Phase Power: 5.28 KW

Continuous Single Phase Power: 4.8 KW

Max Three Phase Power: 8.6 KW

Continuous Three Phase Power: 8 KW

Fuel: Diesel

Voltage: 230 V / 400 V

Frequency: 50 Hz

Engine: Yanmar 3TNV70-HGE

Start: Electric

Consumption: 3.45 Lt/h at 100% load

Dimensions: Length: 1400 mm, Width: 650 mm, Height: 975 mm

Weight: 325 Kg

Compound Voltage Regulator



CONTROL PANEL

Controls:

- Start Key: OFF - ON - START
- Star-delta power switch

Instruments:

- Voltmeter
- Hour meter
- Low oil pressure indicator

Protections:

- Circuit Breaker
- Automatic with switching (AMF)

Outlets:

- 1 2P+T CEE 230V 16A IP44
- 1 2P+T CEE 230V 32A IP44
- 1 3P+N+T CEE 400V 16A IP44

The PRAMAC P11000 power generator is a professional diesel generator developed by Pramac with a soundproofed casing, ideal for residential areas. With its quiet operation, it is the ideal generator for use in residential areas or outside of working hours. The P11000 generator is equipped with top-quality components and complete instrumentation for use on construction sites or to address potential blackouts.

If you are looking for a generator like the P11000 AMF single/three phase power generator, we recommend browsing our range of ground generators to find the one that best suits your needs.

Images and technical data are indicative only.



Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 5.28

Continuous power single phase (KW): 4.8

Maximum power single phase (KVA): 6.6

Continuous power single phase (KVA): 6

Maximum power three phase (KW): 8.6

Continuous power three phase (KW): 8

Maximum power three phase (KVA): 10.8

Continuous power three phase (KVA): 10

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Sockets configuration: 1 x 400V 16A 3P+N+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A 2P+T CEE

Engine: Yanmar 3TNV70-HGE, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 854

Oil capacity (L): 3.8

Cooling: Water

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 2.65 at 75% of the load / 3.45 at 100% of the load

Running time (h): 9.06 at 75% of the load / 6.96 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 1400

Width (mm): 650

Height (mm): 975

Dry weight (Kg): 325

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Yes

Voltage regulator: Compound

Engine manufacturer: Yanmar