



# PRAMAC P4500

## Product description:

## Product features:

Phase: Single phase

Maximum power single phase (KW): 3.7

Continuous power single phase (KW): 3.1

Maximum power single phase (KVA): 4.1

Continuous power single phase (KVA): 3.5

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Yanmar L70N Electric, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 320

Oil capacity (L): 1.1

Cooling: Air

Poles: 2

Fuel tank capacity (L): 18

Consumption (L/h): 0.93 at 75% of the load / 1.24 at 100% of the load

Running time (h): 19.35 at 75% of the load / 14.52 at 100% of the load

Acoustic power: 96 dB(A)

Acoustic pressure: 68 dB(A) at 7 m

Length (mm): 800

Width (mm): 520



Height (mm): 690

Dry weight (Kg): 99

Silenced: Yes

Super silenced: No

Product type: Generator

ATS Switch device : Optional

Voltage regulator: Capacitor

Engine manufacturer: Yanmar