



PRAMAC P9000 SINGLE PHASE DPP AVR



Product description:

Product features:

Phase: Single phase

Maximum power single phase (KW): 7.9

Continuous power single phase (KW): 6.8

Maximum power single phase (KVA): 8.8

Continuous power single phase (KVA): 7.6

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230

Sockets configuration: 1 x 230V 16A 2P+T CEE - 1 x 230V 32A 2P+T CEE - 1 x 230V 16A SCHUKO

Engine: Lombardini 25LD330, naturally aspirated

Engine rpm (rpm): 3000

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 654

Oil capacity (L): 1.8

Cooling: Air

Alternator: Brushless

Poles: 2

Fuel tank capacity (L): 24

Consumption (L/h): 2.17 at 75% of the load / 2.90 at 100% of the load

Running time (h): 11.06 at 75% of the load / 8.25 at 100% of the load

Acoustic power: 97 dB(A)

Acoustic pressure: 69 dB(A) at 7 m

Length (mm): 990





Width (mm): 602
Height (mm): 826
Dry weight (Kg): 204
Silenced: Yes
Super silenced: No
Product type: Generator
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: Lombardini