

WFM SE12000-MTHE AVR



Product description:

Product features:

Phase: Single phase / Three phase
Maximum power single phase (KW): 8.8
Continuous power single phase (KW): 7.9
Maximum power single phase (KVA): 11
Continuous power single phase (KVA): 9.9
Maximum power three phase (KW): 26.4
Continuous power three phase (KW): 24
Maximum power three phase (KVA): 33
Continuous power three phase (KVA): 30
Fuel: Diesel
Frequency (Hz): 50
Voltage (V): 230 / 400
Engine: John Deere 3029 DF 128, naturally aspirated
Engine rpm (rpm): 1500
Speed governor: Mechanical
Starting system: Electric
Engine capacity (cm³): 2900
Number cylinders: 3
Cooling: Water
Alternator: Mecc Alte ECO 28 VL4, brushless
Poles: 4
Bore x stroke (mm): 106 x 110
Fuel tank capacity (L): 135
Consumption (L/h): 7 at 100% of the load
Running time (h): 19.28 at 100% of the load

Acoustic pressure: 67 dB(A) at 7 m
Length (mm): 1940
Width (mm): 1000
Height (mm): 1480
Dry weight (Kg): 960
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: John Deere