

WFM SE12000-MTHE AVR



Product description:

Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 11.7

Continuous power single phase (KW): 10.6

Maximum power single phase (KVA): 14.6

Continuous power single phase (KVA): 13.4

Maximum power three phase (KW): 35.2

Continuous power three phase (KW): 32

Maximum power three phase (KVA): 44

Continuous power three phase (KVA): 40

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: John Deere 3029 TF 158, turbocharged

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm³): 2900

Number cylinders: 3

Cooling: Water

Alternator: Mecc Alte ECO 32 3S, brushless

Poles: 4

Bore x stroke (mm): 106 x 110

Fuel tank capacity (L): 135

Consumption (L/h): 8 at 100% of the load

Running time (h): 16.87 at 100% of the load

Acoustic pressure: 67 dB(A) at 7 m
Length (mm): 1940
Width (mm): 1000
Height (mm): 1480
Dry weight (Kg): 1020
Silenced: Yes
Super silenced: Yes
ATS Switch device : Optional
Voltage regulator: AVR
Engine manufacturer: John Deere