



# WFM SE12000-MTHE AVR

## Product description:

## Product features:

Phase: Single phase / Three phase

Maximum power single phase (KW): 13.3

Continuous power single phase (KW): 18

Maximum power single phase (KVA): 16

Continuous power single phase (KVA): 22.5

Maximum power three phase (KW): 40

Continuous power three phase (KW): 36

Maximum power three phase (KVA): 50

Continuous power three phase (KVA): 45

Fuel: Diesel

Frequency (Hz): 50

Voltage (V): 230 / 400

Engine: PERKINS 1103A-33TG1, aspirazione sovralimentata

Engine rpm (rpm): 1500

Speed governor: Mechanical

Starting system: Electric

Engine capacity (cm<sup>3</sup>): 3300

Number cylinders: 3

Cooling: Water

Alternator: Leroy Somer LSA43.2 S25, brushless

Poles: 4

Bore x stroke (mm): 105 x 127

Fuel tank capacity (L): 135

Consumption (L/h): 9 at 100% of the load

Running time (h): 15 at 100% of the load

---

Acoustic pressure: 67 dB(A) at 7 m  
Length (mm): 1940  
Width (mm): 1000  
Height (mm): 1480  
Dry weight (Kg): 1200  
Silenced: Yes  
Super silenced: Yes  
ATS Switch device : Optional  
Voltage regulator: AVR  
Engine manufacturer: Perkins