



# GENSET MG 3000 I-HE - GENERATOR 3 KVA

Product price:

**690,00 € tax excluded**

## Product description:

GENSET MG 3000 I-HE GENERATOR SINGLEPHASE 3 KVA

The generator GENSET MG 3000 I-HE singlephase is equipped with a gasoline engine capable of delivering 3 KVA with voltage regulator.

The GENSET MG 3000 I-HE single-phase generator provides reliable power for home, work and recreation environments. Safely powering appliances and other electronic devices solution for outdoor parties.

Generator is as easy to install and operate as it is to start and stop thanks to clear, intuitive controls (pull start) Auto shut-off for low oil level Durable frame.

GENSET MG 3000 I-HE has an all-steel construction and a large metal tank with fill indicator. The generator provides efficient and quiet operation thanks to the Honda OHV engine that allows to deliver a maximum power of 3 KVA.

## TECHNICAL FEATURES GENSET MG 3000 I-HE

Phase Type: SinglePhase

Maximum SinglePhase Output: 3 KVA

Maximum SinglePhase Output: 2.4 KW

VAC Voltage: 230 V

Frequency (Hz): 50

Quadro Starter: Manual with self-winding

Motor: Honda GX 160 OHV

Emission Standard: Stage V

RPM: 3000

Power supply: Gasoline

Fuel tank capacity: 3.1 l



Consumption @ 75 % load: 1.4 l/h  
Autonomy @ 50 % load: 2.21 h  
Sound pressure: 95 dB(A) @ 7m  
Length: 610 mm  
Width: 360 mm  
Height: 410 mm  
Net weight: 36 Kg

Looking for a generator with different characteristics? Here you can find the full range of generators GENSET or other specialized brands

Images and technical data are not binding.

#### **Product features:**

Phase: Single phase  
Maximum power single phase (KW): 2.4  
Maximum power single phase (KVA): 3  
Fuel: Gasoline  
Frequency (Hz): 50  
Voltage (V): 230  
Sockets configuration: 2 Schuko  
Engine: Honda GX160, 4 stroke, OHV  
Emissions Regulations: Stage 5  
Engine rpm (rpm): 3000  
Ignition: Recoil  
Starting system: Manual  
Engine capacity (cm<sup>3</sup>): 163  
Number cylinders: 1  
Cooling: Air  
Protection degree: IP23  
Motor insulation class: H  
Fuel tank capacity (L): 3.1  
Consumption (L/h): 1.4  
Running time (h): 2.21  
Acoustic power: 95 dB(A)  
Acoustic pressure: 70 dB(A) at 7 m  
Length (mm): 610  
Width (mm): 360  
Height (mm): 410  
Dry weight (Kg): 36  
Silenced: No  
Super silenced: No

Product type: Generator

ATS Switch device : No

Voltage regulator: No

Engine manufacturer: Honda